

# WORK BOOK 2024



superior.





## PŘÍBĚH ZNAČKY

Naše mise je vytvářet moderní kola, která inspirují aktivní lidi prostřednictvím progresivního a špičkového designu, vysoké kvality zpracování a pozornosti k detailům. Vytváříme moderní kola, která dodávají elán novým cyklistům a pomáhají těm stávajícím jezdit rychleji, pohodlněji a šťastněji. Inspirujeme aktivní lidi, aby milovali cyklistiku stejně jako my.



## CÍLOVÁ SKUPINA

Definujeme naši cílovou skupinu jako „aktivní lidi“. Jedná se o lidi, kteří jezdí na kole při sportovních příležitostech, ať už jsou to nadšení závodníci, kteří usilují o umístění na stupních vítězů, čistokrevní sportovci, kteří usilují o úspěchy, nebo lidé jezdící do práce. Všichni jezdí buď z fyzických nebo mentálních potřeb, a to jak na standardních kolech, tak na kolech elektrických. Z hlediska sociálně-demografického pohledu pocházejí tito lidé ze skupiny tzv. „městské střední třídy“. Tito lidé žijí moderním životem, zaměřují se na zdraví, vzdělání a věří v tvrdou práci. S rostoucí kupní silou tato skupina aspiruje na kvalitní a značkové produkty.





## BENEFITY ZNAČKY

**Naše tři výhody jsou:**

**1. SUPERIOR JÍZDA** / Díky vlastnímu vývoji a spolupráci s předními dodavateli dokážeme navrhovat a vyvíjet lehká a rychlá kola pro různé příležitosti. Máme 6 různých řad modelů, od horských kol po městská kola. Společným znakem je, že naše kola jsou moderní, rychlá a mají čistý a jednoduchý design.

**2. SUPERIOR MOMENT** / Dodáváme nejen produkt, ale také emoce. Cyklistika je o čistých emocích, pocitech, které si užíváme při jízdě na našich kolech. Jednou z klíčových emocí je pocit úspěchu. S našimi koly podporujeme a posouváme cyklisty, aby usilovali o tyto emoce.

**3. SUPERIOR ZÁKAZNICKÁ PÉČE** / Podívali jsme se na chování zákazníků a zjistili jsme, že 80% zákazníků bere v úvahu nejen kolo, ale i veškeré informace související s koly - jako je webová stránka, komunikace, prodejci. Až 90% zákazníků je ochotno opustit značku po pouhých 2 negativních zkušenostech. Chceme našim zákazníkům poskytnout nejlepší zážitek na cestě: začíná to hledáním kol, pokračuje nákupem a končí jízdou.



## RTB

### HISTORIE

Česká značka vyráběná v podhůří Beskyd od roku 1993.

### TÝMY

Kvalita testována a prokázána týmy Elite XCO jb Brunex a dalšími týmy.

### VÝVOJ A DESIGN

Vlastní vývoj a design.

### MATERIÁLY A KOMPONENTY

Používáme nejlepší materiály a komponenty.



# NOVÉ NÁZVOSLOVÍ

MATERIÁL RÁMU

9

Karbon

6

Hliník

ÚROVEŇ KOMPONENTŮ

9

Nejvyšší



1

Nejnižší

KATEGORIE ELEKTROKOLA

e

Silná elektrokola

i

Lehká elektrokola

POUŽITÍ

Team

Team modely

RC

Race

DC

Down Country

GF

Gran Fondo

GR

Gravel

SUV

Sport Utility

PŘÍKLAD

# XF 9.9 Team

Modelová  
řada

Materiál  
rámu

Úroveň  
komponentů

Využití



## NOVÝ MODEL

## SOUČASNÝ NÁZEV

MTB FULL SUSPENSION		
<b>XF TEAM</b>		
XF 9.9 TEAM		TEAM XF 29 FACTORY RACING
XF 9.8 TEAM		TEAM XF 29 ISSUE R
XF 9.7 TEAM		NOVÝ MODEL
XF 9.6 TEAM		TEAM XF 29 ISSUE
XF 9.5 TEAM		TEAM XF 29 ELITE
<b>XF RC</b>		
XF 9.7 RC		XF 979 RC
XF 9.6 RC		XF 969 RC
XF 9.2 RC		XF 929 RC
<b>XF DC</b>		
XF 9.7 DC		XF 979 TR
XF 9.6 DC		XF 969 TR
XF 9.2 DC		XF 929 TR
XF 6.6 DC		XF 939 TR
XF 6.2 DC		XF 919 TR
MTB HARDTAIL		
<b>TEAM</b>		
XP 9.8 TEAM		TEAM 29 ISSUE
XP 9.5 TEAM		TEAM 29 ELITE
<b>XP</b>		
XP 9.7		XP 979
XP 9.6		XP 969
XP 9.2		XP 929
ROAD		
<b>GRAN FONDO</b>		
X-ROAD 9.8 GF		X-ROAD TEAM ISSUE R
X-ROAD 9.7 GF		X-ROAD TEAM ISSUE D12
X-ROAD 9.5 GF		X-ROAD TEAM ELITE D12
X-ROAD 9.3 GF		X-ROAD TEAM COMP
X-ROAD 6.5 GF		X-ROAD ISSUE
X-ROAD 6.3 GF		X-ROAD COMP
<b>GRAVEL</b>		
X-ROAD 9.7 GR		X-ROAD TEAM ISSUE GR
X-ROAD 9.5 GR		X-ROAD TEAM COMP GR
X-ROAD 6.5 GR		X-ROAD ISSUE GR
X-ROAD 6.3 GR		X-ROAD COMP GR
iMTB FULL SUSPENSION   Lehké		
<b>iXF</b>		
iXF 9.8		NOVÝ MODEL
iXF 9.7		NOVÝ MODEL
iXF 9.6		NOVÝ MODEL
iXF 9.2		NOVÝ MODEL
iTOUR   Lehké		
<b>iBLOX</b>		
iBLOX 6.6		NOVÝ MODEL
iBLOX 6.5		NOVÝ MODEL
iBLOX 6.3		NOVÝ MODEL
iGRAVEL   Lehké		
<b>iX-ROAD</b>		
iXR 6.7		NOVÝ MODEL
iXR 6.5		NOVÝ MODEL
eMTB FULL SUSPENSION		
<b>eXF</b>		
eXF 6.8		eXF 9049 B
eXF 6.5		eXF 9019 B
eXF 6.2		eXF 8089 B
eXF 6.2 SUV		eXF 8089 B SUV
eMTB HARDTAIL		
<b>eXC</b>		
eXC 6.3		eXC 7039 B
eTOUR		
<b>eBLOX</b>		
eBLOX 6.5		eXR 6090 B
eBLOX 6.3		eXR 6070 B
eBLOX 6.1		eXR 6050 B
<b>eWAY</b>		
eWAY 6.6		SBT 600
eWAY 6.5		SBC 450
eWAY 6.2		SBC 400



# MTB CELOODPRUŽENÉ / MODEL MATRIX



XF TEAM



XF RC



XF DC

	RÁM		VIDLICE					ZDVIH			ZADNÍ TLUMIČ				VÝPLETY			PLÁŠTĚ		KOKPIT			KOMPONENTY	POČET PŘEVODŮ						
	MATERIÁL		MODEL					MODEL						MODEL / MATERIÁL			SIZE													
<b>XF TEAM</b>	CARBON HI-MODULUS	ALLOY X6 ULTRALITE	ROCK SHOX SID ULTIMATE	DT SWISS F232 ONE	ROCK SHOX RECON SILVER	ROCK SHOX PIKE ULTIMATE	ROCK SHOX PIKE SELECT	ROCK SHOX 35 SILVER	100mm	110mm	130mm	ROCK SHOX SID LUXE ULTIMATE	DT SWISS R232 ONE	ROCK SHOX DELUXE ULTIMATE RCT	ROCK SHOX DELUXE SELECT	HDK AF2 TWIN	110mm	130mm	DT SWISS XRC 1501 SPLINE   CARBON	DT SWISS XM 1700 SPLINE   ALLOY	DT SWISS M 1900 SPLINE   ALLOY	BLACK JACK / SHIMANO TC500	2,25"	2,4"	CARBON MTB COMBO	ALLOY MTB-RACE	ALLOY MTB-DOWN COUNTRY			
XF 9.9 Team	•		•						•			•						•					•					SRAM XX SL EAGLE AXS   BR SHIMANO XTR 9100	12	
XF 9.8 Team	•			•					•				•					•					•					SHIMANO XTR   BR SHIMANO XTR 9100	12	
XF 9.7 Team	•		•						•			•						•	•				•					SRAM XO EAGLE AXS   BR SHIMANO XTR 9100	12	
XF 9.6 Team	•			•					•			•						•	•				•					SHIMANO XTR   BR SHIMANO XTR 9100	12	
XF 9.5 Team	•			•					•			•						•	•				•					SHIMANO XT   BR SHIMANO XT 8100	12	
<b>XF RC</b>																														
XF 9.7 RC	•			•					•			•							•				•						SHIMANO XT-SLX   BR SHIMANO XT 8100	12
XF 9.6 RC	•			•					•			•							•				•						SHIMANO SLX   BR SHIMANO M6100	12
XF 9.2 RC	•				•			•				•						•	•				•						SHIMANO DEORE   BR SHIMANO M4101	12
<b>XF DC</b>																														
XF 9.7 DC	•					•			•			•							•				•			•			SHIMANO XT-SLX   BR SHIMANO XT 8120 4 pístkové	12
XF 9.6 DC	•					•			•			•							•				•			•			SHIMANO SLX   BR SHIMANO M6120 4 pístkové	12
XF 9.2 DC	•							•	•			•						•	•				•			•			SHIMANO DEORE   BR SHIMANO M420 4 pístkové	12
XF 6.6 DC		•							•			•							•				•						SHIMANO SLX   BR SHIMANO M420 4 pístkové	12
XF 6.2 DC		•						•	•			•							•				•						SHIMANO DEORE   BR SHIMANO M420 4 pístkové	12



# MTB HARDTAIL / MODEL MATRIX



XP TEAM



XP

	RÁM	VIDLICE			ZDVIH	VÝPLETY			PLÁŠŤĚ SIZE	KOKPIT		KOMPONENTY	POČET PŘEVODŮ
	MATERIÁL	MODEL				MODEL / MATERIÁL							
	CARBON MID-MODULUS	DT SWISS F232 ONE	ROCK SHOX, SID SL	ROCK SHOX RECON SILVER	100mm	DT SWISS XR 1700 SPLINE   CARBON	DT SWISS X 1900 SPLINE   ALLOY	BLACK JACK / SHIMANO TC500	2,25"	CARBON MTB COMBO	ALLOY MTB-RACE		
<b>XP TEAM</b>													
XP 9.8 Team	•	•			•	•			•	•		SHIMANO XTR   BR SHIMANO XTR 9100	12
XP 9.5 Team	•	•			•	•			•		•	SHIMANO XT   BR SHIMANO XT 8100	12
<b>XP</b>													
XP 9.7	•	•			•		•		•		•	SHIMANO XT-SLX   BR SHIMANO XT 8100	12
XP 9.6	•		•		•		•		•		•	SHIMANO SLX   BR SHIMANO M6100	12
XP 9.2	•			•	•			•	•		•	SHIMANO DEORE   BR SHIMANO MT410	12



# ROAD & GRAVEL / MODEL MATRIX



X-ROAD GRAN FONDO



X-ROAD GRAVEL

	RÁM MATERIÁL		VÝPLETY MODEL / MATERIÁL							PLÁŠTĚ SIZE			KOKPIT		KOMPONENTY	POČET PŘEVODŮ
	CARBON MID-MODULUS	ALLOY X6 ULTRALITE	DT SWISS ERC 1400 DICUT   CARBON	DT SWISS ER 1600 SPLINE   ALLOY	DT SWISS GR 1600 SPLINE   ALLOY	DT SWISS C 1800 SPLINE   ALLOY	DT SWISS, G 1800 SPLINE   ALLOY	DT SWISS R500 Disc / SHIMANO RS470CL	STARS J22GT Disc, Shimano RS470CL	30mm	32mm	40mm	CARBON ROAD COMBO	ALLOY ROAD RACE		
<b>X-ROAD GRAN FONDO</b>																
X-ROAD 9.8 GF	•		•							•			•		SHIMANO ULTEGRA Di2	2x12
X-ROAD 9.7 GF	•			•						•			•		SHIMANO ULTEGRA Di2	2x12
X-ROAD 9.5 GF	•						•			•				•	SHIMANO 105 Di2	2x12
X-ROAD 9.3 GF	•						•			•				•	SHIMANO 105	2x12
X-ROAD 6.5 GF		•								•				•	SHIMANO 105	2x12
X-ROAD 6.3 GF		•									•			•	SHIMANO TIAGRA	2x10
<b>X-ROAD GRAVEL</b>																
X-ROAD 9.7 GR	•				•							•	•		SHIMANO GRX820	12
X-ROAD 9.5 GR	•							•				•		•	SHIMANO GRX610	12
X-ROAD 6.5 GR		•										•		•	SHIMANO GRX610	12
X-ROAD 6.3 GR		•										•		•	SHIMANO GRX400	10

# LEHKÁ ELEKTROKOLA / MODEL MATRIX



iXF



iBLOX



iXR

	RÁM		E DRIVE SYSTEM					VIDLICE					ZADNÍ TLUMIČ		VÝPLETY			PLÁŠŤĚ			KOKPIT	KOMPONENTY	POČET PŘEVODŮ													
	MATERIÁL							MODEL	ZDVIH	MODEL	ZDVIH	MODEL / MATERIÁL	SIZE																							
	CARBON HI-MODULUS	ALLOY X6	BOSCH SX PERFORMANCE	DISPLAY MINI REMOTE	DISPLAY MINI REMOTE DROP BAR	DISPLAY KIOX 300	BATTERY COMPACT TUBE 400Wh	CHARGER 2A	DT SWISS F535 ONE	ROCK SHOX 35 SILVER	ROCK SHOX JUDY SILVER	RST VOLANT	ROCK SHOX RUDY	RIGID VIDLICE ALLOY	MONOSHOCK ALLOY	45mm	80mm	100mm	140mm	150mm	DT SWISS R535 ONE	ROCK SHOX DELUXE SELECT	140mm	DT SWISS HYBRID MTB HXC 1501   CARBON	DT SWISS HYBRID MTB H 1900 SPLINE   ALLOY	DT SWISS HG 1800 SPLINE   ALLOY	BLACK JACK / SHIMANO TC500	STARS J25DH Disc / SHIMANO TC500	2,4"	2,25"	45mm	CARBON MTB COMBO	ALLOY MTB DOWN COUNTRY	TOURING SPORT	ALLOY ROAD RACE	
<b>iXF</b>																																				
iXF 9.8	•		•	•			•	•	•											•	•	•	•												SHIMANO XT - Di2   BR SHIMANO XT 8120 4 pístkové	12
iXF 9.7	•		•	•			•	•	•											•	•	•	•											SHIMANO XT-SLX   BR SHIMANO XT 8120 4 pístkové	12	
iXF 9.6	•		•	•			•	•	•											•	•	•	•											SHIMANO SLX   BR SHIMANO M6120 4 pístkové	12	
iXF 9.2	•		•	•			•	•	•	•										•	•	•	•											SHIMANO DEORE   BR SHIMANO M420 4 pístkové	12	
<b>iBLOX</b>																																				
iBLOX 6.6		•	•				•	•	•						•																				SHIMANO DEORE   BR SHIMANO M420 4 pístkové	12
iBLOX 6.5		•	•				•	•	•																										SHIMANO DEORE   BR SHIMANO M420 4 pístkové	12
iBLOX 6.3		•	•				•	•	•		•																								SHIMANO CUES   BR SHIMANO MT200	11
<b>iXR</b>																																				
iXR 6.7		•	•				•	•																											SHIMANO GRX825 Di2	12
iXR 6.5		•	•				•	•																											SHIMANO GRX610	12



# E DRIVE SYSTEM / MODEL MATRIX



eXF

eXC

eBLOX

eWAY

	E DRIVE SYSTEM											PLÁŠŤĚ SIZE				VIDLICE ZDVIH					KOMPONENTY	POČET PŘEVODŮ	
	BOSCH CX PERFORMANCE	BOSCH PERFORMANCE	BOSCH ACTIVE PLUS	DISPLAY MINI REMOTE	DISPLAY KIOX 300	DISPLAY INTUVIA 100	DISPLAY PURION 200	BATTERY POWER TUBE 750Wh	BATTERY POWER TUBE 625Wh	BATTERY POWER TUBE 500Wh	CHARGER 4A	CHARGER 2A	2,6"	2,35"	2,25"	2,0"	50mm	80mm	100mm	140mm			160mm
<b>eXF</b>																							
eXF 6.8	•			•			•			•		•									•	SHIMANO XT-   BR SHIMANO XT 8120 4 pístkové	12
eXF 6.5	•			•			•			•		•									•	SHIMANO DEORE   BR SHIMANO M420 4 pístkové	12
eXF 6.2	•			•				•		•		•									•	SHIMANO DEORE   BR SHIMANO M420 4 pístkové	12
eXF 6.2 SUV	•				•			•		•			•								•	SHIMANO DEORE   BR SHIMANO M420 4 pístkové	12
<b>eXC</b>																							
eXC 6.3		•				•		•			•			•							•	SHIMANO CUES   BR SHIMANO MT200	11
<b>eBLOX</b>																							
eBLOX 6.5	•				•		•			•				•							•	SHIMANO DEORE   BR SHIMANO M420 4 pístkové	12
eBLOX 6.3		•				•		•			•										•	SHIMANO CUES   BR SHIMANO MT200	11
eBLOX 6.1			•			•			•		•			•							•	SHIMANO CUES   BR SHIMANO MT200	9
<b>eWAY</b>																							
eWAY 6.6		•				•		•			•			•	•							SHIMANO CUES   BR SHIMANO MT200	10
eWAY 6.5		•				•		•			•			•	•							SHIMANO NEXUS   CARBON DRIVE   BR SHIMANO MT200	8
eWAY 6.2			•			•			•		•			•	•							SHIMANO NEXUS   BR SHIMANO MT200	7

# XF 9.9 Team

Gloss Red Carbon / Black

MTB FULL-SUSPENSION / XF TEAM



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 MTB bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### FRAMESET

FRAME	Carbon MTB Race Pro SU-01.2, Advanced Race Geometry, Travel 110 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	RockShox SID Ultimate Charger RD R, Tapered, DebonAir, 15x110mm axle, 110mm travel
REAR SHOCK	RockShox SIDLuxe Ultimate Remote, size 190x40mm
BOTTOM BRACKET	SRAM DUB, PressFit, shell 41x92 mm
HEADSET	ACROS AZX-1052S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	BOOST UDH LIGHT, SB01-LT, TA12x175.5, M12x1,0x14.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SRAM AXS ROCKER, 12-speed
REAR DERAILLEUR	SRAM XX EAGLE AXS T-Type
CRANKSET	SRAM XX, DUB, Carbon, T-Type, 36T
CASSETTE	SRAM XX XS-1299, 12-speed, T-Type, 10-52T
CHAIN	SRAM XX, T-Type

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO XTR M9100, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-MT900, 180mm
BRAKES REAR	SHIMANO XTR M9100, hydraulic disc brake
ROTOR REAR	SHIMANO RT-MT900, 160mm

### WHEELS

WHEELSET FRONT	DT Swiss XRC 1501 SPLINE®, Carbon, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss XRC 1501 SPLINE®, Carbon, CL, 12x148mm, SRAM XD, Tubeless Ready
TYRES FRONT	Schwalbe Racing Ray Evo, TL-Easy, SuperRace, 29x2.25", ADDIX Speed
TYRES REAR	Schwalbe Racing Ralph Evo, TL-Easy, SuperRace, 29x2.25", ADDIX Speed

### COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

### PARTS

SADDLE	Fizik Ridon X1, Carbon
SEAT POST LEVER	SRAM AXS ROCKER, Dropper Post Lever
SEATPOST	SRAM Reverb AXS dropper post, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

## GEOMETRY

FRAME SIZE	S	M	L	XI
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	580	605	625	645
STACK HEIGHT (mm) ToUpper()	583	593	602	611
REACH (mm) ToUpper()	439	460	478	496
SEAT TUBE ANGLE ToUpper()	76,3°	76,3°	76,3°	76,3°
HEAD TUBE ANGLE ToUpper()	66,5°	66,5°	66,5°	66,5°
REAR CENTER (mm) ToUpper()	430	430	430	430
HEAD TUBE LENGTH (mm) ToUpper()	90	100	110	120
WHEELBASE (mm) ToUpper()	1153	1179	1200	1222

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



# XF 9.8 Team

Gloss Red Carbon / Black

MTB FULL-SUSPENSION / XF TEAM



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 MTB bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### FRAMESET

FRAME	Carbon MTB Race Pro SU-01.2, Advanced Race Geometry, Travel 110 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	DT Swiss F232 ONE, Tapered, 15x110mm axle, 110mm travel
REAR SHOCK	DT Swiss R232 ONE, size 190x40mm
BOTTOM BRACKET	SHIMANO BB-71-41A, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1052S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	BOOST UDH LIGHT, SB01-LT, TA12x175.5, M12x1,0x14.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO XTR SL-M9100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO XTR RD-M9100, Shadow Plus Design
CRANKSET	SHIMANO XTR FC-M9120, Hollowtech II, 36T
CASSETTE	SHIMANO XTR CS-M9101, 12-speed, 10-51T
CHAIN	SHIMANO XT CN-M8100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO XTR M9100, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-MT900, 160mm
BRAKES REAR	SHIMANO XTR M9100, hydraulic disc brake
ROTOR REAR	SHIMANO RT-MT900, 160mm

### WHEELS

WHEELSET FRONT	DT Swiss XRC 1501 SPLINE®, Carbon, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss XRC 1501 SPLINE®, Carbon, CL, 12x148mm, SH12, Tubeless Ready
TYRES FRONT	Schwalbe Racing Ray Evo, TL-Easy, SuperRace, 29x2.25", ADDIX Speed
TYRES REAR	Schwalbe Racing Ralph Evo, TL-Easy, SuperRace, 29x2.25", ADDIX Speed

### COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

### PARTS

SADDLE	Fizik Ridon X1, Carbon
SEAT POST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	Crankbrothers Highline 11 dropper post, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

## GEOMETRY

FRAME SIZE	S	M	L	XL
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	580	605	625	645
STACK HEIGHT (mm) ToUpper()	583	593	602	611
REACH (mm) ToUpper()	439	460	478	496
SEAT TUBE ANGLE ToUpper()	76,3°	76,3°	76,3°	76,3°
HEAD TUBE ANGLE ToUpper()	66,5°	66,5°	66,5°	66,5°
REAR CENTER (mm) ToUpper()	430	430	430	430
HEAD TUBE LENGTH (mm) ToUpper()	90	100	110	120
WHEELBASE (mm) ToUpper()	1153	1179	1200	1222

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# XF 9.7 Team

Gloss Red Carbon / Black

MTB FULL-SUSPENSION / XF TEAM



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 MTB bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### FRAMESET

FRAME	Carbon MTB Race Pro SU-01.2, Advanced Race Geometry, Travel 110 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	RockShox SID Ultimate Charger RD R, Tapered, DebonAir, 15x110mm axle, 110mm travel
REAR SHOCK	RockShox SIDLuxe Ultimate Remote, size 190x40mm
BOTTOM BRACKET	SRAM DUB, PressFit, shell 41x92 mm
HEADSET	ACROS AZX-1052S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	BOOST UDH LIGHT, SB01-LT, TA12x175.5, M12x1,0x14.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SRAM AXS ROCKER, 12-speed
REAR DERAILLEUR	SRAM X0 EAGLE AXS T-Type
CRANKSET	SRAM X0, DUB, Carbon, T-Type, 34T
CASSETTE	SRAM X0 XS-1295, 12-speed, T-Type, 10-52T
CHAIN	SRAM X0, T-Type

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO XTR M9100, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-MT900, 180mm
BRAKES REAR	SHIMANO XTR M9100, hydraulic disc brake
ROTOR REAR	SHIMANO RT-MT900, 160mm

### WHEELS

WHEELSET FRONT	DT Swiss XM 1700 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss XM 1700 SPLINE®, CL, 12x148mm, SRAM XD, Tubeless Ready
TYRES FRONT	Schwalbe Racing Ray Evo, TL-Easy, SuperRace, 29x2.25", ADDIX Speed
TYRES REAR	Schwalbe Racing Ralph Evo, TL-Easy, SuperRace, 29x2.25", ADDIX Speed

### COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

### PARTS

SADDLE	Fizik Ridon X3, Kium
SEAT POST LEVER	SRAM AXS ROCKER, Dropper Post Lever
SEATPOST	SRAM Reverb AXS dropper post, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

## GEOMETRY

FRAME SIZE	S	M	L	XL
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	580	605	625	645
STACK HEIGHT (mm) ToUpper()	583	593	602	611
REACH (mm) ToUpper()	439	460	478	496
SEAT TUBE ANGLE ToUpper()	76,3°	76,3°	76,3°	76,3°
HEAD TUBE ANGLE ToUpper()	66,5°	66,5°	66,5°	66,5°
REAR CENTER (mm) ToUpper()	430	430	430	430
HEAD TUBE LENGTH (mm) ToUpper()	90	100	110	120
WHEELBASE (mm) ToUpper()	1153	1179	1200	1222

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



# XF 9.6 Team

Gloss Red Carbon / Black

MTB FULL-SUSPENSION / XF TEAM



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 MTB bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### FRAMESET

FRAME	Carbon MTB Race Pro SU-01.2, Advanced Race Geometry, Travel 110 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	DT Swiss F232 ONE, Tapered, 15x110mm axle, 110mm travel
REAR SHOCK	DT Swiss R232 ONE, size 190x40mm
BOTTOM BRACKET	SHIMANO BB-71-41A, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1052S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	BOOST UDH LIGHT, SB01-LT, TA12x175.5, M12x1,0x14.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO XTR SL-M9100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO XTR RD-M9100, Shadow Plus Design
CRANKSET	SHIMANO XTR FC-M9120, Hollowtech II, 36T
CASSETTE	SHIMANO XT CS-M8100, 12-speed, 10-51T
CHAIN	SHIMANO XT CN-M8100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO XTR M9100, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-MT800, 160mm
BRAKES REAR	SHIMANO XTR M9100, hydraulic disc brake
ROTOR REAR	SHIMANO RT-MT800, 160mm

### WHEELS

WHEELSET FRONT	DT Swiss XM 1700 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss XM 1700 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TYRES FRONT	Schwalbe Racing Ray Evo, SuperGround, TL-Easy, 29x2.25", ADDIX SpeedGrip
TYRES REAR	Schwalbe Racing Ralph Evo, SuperGround, TL-Easy, 29x2.25", ADDIX Speed

### COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

### PARTS

SADDLE	Fizik Ridon X5, Alloy
SEAT POST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	Crankbrothers Highline 7 dropper post, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

## GEOMETRY

FRAME SIZE	S	M	L	XL
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	580	605	625	645
STACK HEIGHT (mm) ToUpper()	583	593	602	611
REACH (mm) ToUpper()	439	460	478	496
SEAT TUBE ANGLE ToUpper()	76,3°	76,3°	76,3°	76,3°
HEAD TUBE ANGLE ToUpper()	66,5°	66,5°	66,5°	66,5°
REAR CENTER (mm) ToUpper()	430	430	430	430
HEAD TUBE LENGTH (mm) ToUpper()	90	100	110	120
WHEELBASE (mm) ToUpper()	1153	1179	1200	1222

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# XF 9.5 Team

Gloss Red Carbon / Black

MTB FULL-SUSPENSION / XF TEAM



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 MTB bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### FRAMESET

FRAME	Carbon MTB Race Pro SU-01.2, Advanced Race Geometry, Travel 110 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	DT Swiss F232 ONE, Tapered, 15x110mm axle, 110mm travel
REAR SHOCK	DT Swiss R232 ONE, size 190x40mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1090S ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, STAINLESS BEARINGS, BLACK
REAR AXLE	BOOST UDH LIGHT, SB01-LT, TA12x175.5, M12x1,0x14.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE XT SL-M8100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100, Shadow Plus Design
CRANKSET	SHIMANO XT FC-M8120, Hollowtech II, 36T
CASSETTE	SHIMANO XT CS-M8100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO XT M8100, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-MT800, 160mm
BRAKES REAR	SHIMANO XT M8100, hydraulic disc brake
ROTOR REAR	SHIMANO RT-MT800, 160mm

### WHEELS

WHEELSET FRONT	DT Swiss XM 1700 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss XM 1700 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TYRES FRONT	Schwalbe Racing Ray Performance, TL-Ready, 29x2.25", ADDIX SpeedGrip
TYRES REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 29x2.25", ADDIX

### COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 760mm, 31.8mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

### PARTS

SADDLE	Fizik Ridon X5, Alloy
SEAT POST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

## GEOMETRY

FRAME SIZE	S	M	L	XL
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	580	605	625	645
STACK HEIGHT (mm) ToUpper()	583	593	602	611
REACH (mm) ToUpper()	439	460	478	496
SEAT TUBE ANGLE ToUpper()	76,3°	76,3°	76,3°	76,3°
HEAD TUBE ANGLE ToUpper()	66,5°	66,5°	66,5°	66,5°
REAR CENTER (mm) ToUpper()	430	430	430	430
HEAD TUBE LENGTH (mm) ToUpper()	90	100	110	120
WHEELBASE (mm) ToUpper()	1153	1179	1200	1222

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



# XF 9.7 RC

Matte Carbon

MTB FULL-SUSPENSION / XF RC



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 MTB bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### FRAMESET

FRAME	Carbon MTB Race Pro SU-01.2, Advanced Race Geometry, Travel 110 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	DT Swiss F232 ONE, Tapered, 15x110mm axle, 110mm travel
REAR SHOCK	DT Swiss R232 ONE, size 190x40mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1052S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	BOOST UDH LIGHT, SB01-LT, TA12x175.5, M12x1,0x14.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SLX SL-M7100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100, Shadow Plus Design
CRANKSET	SHIMANO XT FC-M8120, Hollowtech II, 36T
CASSETTE	SHIMANO SLX CS-M7101, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO XT M8100, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 180mm
BRAKES REAR	SHIMANO XT M8100, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 160mm

### WHEELS

WHEELSET FRONT	DT Swiss M 1900 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss M 1900 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TYRES FRONT	Schwalbe Racing Ray Performance, TL-Ready, 29x2.25", ADDIX SpeedGrip
TYRES REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 29x2.25", ADDIX

### COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 760mm, 31.8mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

### PARTS

SADDLE	Fizik Ridon X5, Alloy
SEAT POST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

## GEOMETRY

FRAME SIZE	S	M	L	XL
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	580	605	625	645
STACK HEIGHT (mm) ToUpper()	583	593	602	611
REACH (mm) ToUpper()	439	460	478	496
SEAT TUBE ANGLE ToUpper()	76,3°	76,3°	76,3°	76,3°
HEAD TUBE ANGLE ToUpper()	66,5°	66,5°	66,5°	66,5°
REAR CENTER (mm) ToUpper()	430	430	430	430
HEAD TUBE LENGTH (mm) ToUpper()	90	100	110	120
WHEELBASE (mm) ToUpper()	1153	1179	1200	1222

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# XF 9.6 RC

Gloss Red / Black

MTB FULL-SUSPENSION / XF RC



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 MTB bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### FRAMESET

FRAME	Carbon MTB Race Pro SU-01.2, Advanced Race Geometry, Travel 110 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	DT Swiss F232 ONE, Tapered, 15x110mm axle, 110mm travel
REAR SHOCK	DT Swiss R232 ONE, size 190x40mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1090S ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, STAINLESS BEARINGS, BLACK
REAR AXLE	BOOST UDH LIGHT, SB01-LT, TA12x175.5, M12x1,0x14.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SLX SL-M7100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO SLX RD-M7100, Shadow Plus Design
CRANKSET	SHIMANO SLX FC-M7120, Hollowtech II, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO M6100, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKES REAR	SHIMANO M6100, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

### WHEELS

WHEELSET FRONT	DT Swiss M 1900 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss M 1900 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TYRES FRONT	Schwalbe Racing Ray Performance, TL-Ready, 29x2.25", ADDIX SpeedGrip
TYRES REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 29x2.25", ADDIX

### COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 760mm, 31.8mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

### PARTS

SADDLE	Fizik Ridon X5, Alloy
SEAT POST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

## GEOMETRY

FRAME SIZE	S	M	L	XL
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	580	605	625	645
STACK HEIGHT (mm) ToUpper()	583	593	602	611
REACH (mm) ToUpper()	439	460	478	496
SEAT TUBE ANGLE ToUpper()	76,3°	76,3°	76,3°	76,3°
HEAD TUBE ANGLE ToUpper()	66,5°	66,5°	66,5°	66,5°
REAR CENTER (mm) ToUpper()	430	430	430	430
HEAD TUBE LENGTH (mm) ToUpper()	90	100	110	120
WHEELBASE (mm) ToUpper()	1153	1179	1200	1222

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# XF 9.2 RC

Matte Carbon / White

MTB FULL-SUSPENSION / XF RC



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 MTB bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### FRAMESET

FRAME	Carbon MTB Race Pro SU-01, Advanced Race Geometry, Travel 100 mm, Tapered Head Tube, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	RockShox Recon Silver RL R, Tapered, SoloAir, 15x110mm axle, 100mm travel
REAR SHOCK	DT Swiss R232 ONE, size 190x45mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-220 R4, ZS44/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	BOOST 411K12C1800114, TA12x171.5, M12xP1.5x15.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	SHIMANO FC-MT510, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKES REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

### WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIMS FRONT	BLACK JACK Ready 30, Disc, 32H, Tubeless Ready
TYRES FRONT	Schwalbe Racing Ray Performance, 29x2.25", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIMS REAR	BLACK JACK Ready 30, Disc, 32H, Tubeless Ready
TYRES REAR	Schwalbe Racing Ray Performance, 29x2.25", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Alloy

### COCKPIT

STEM	ONE Race, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 760mm, 31,8mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

### PARTS

SADDLE	Fizi:k Ridon X5, Alloy
SEAT POST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

## GEOMETRY

FRAME SIZE	S	M	L	XL
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	584	610	630	650
STACK HEIGHT (mm) ToUpper()	579	589	597	607
REACH (mm) ToUpper()	427	449	465	482
SEAT TUBE ANGLE ToUpper()	74,9°	74,7°	74,6°	74,5°
HEAD TUBE ANGLE ToUpper()	68°	68°	68°	68°
REAR CENTER (mm) ToUpper()	428	428	428	428
HEAD TUBE LENGTH (mm) ToUpper()	90	100	110	120
WHEELBASE (mm) ToUpper()	1124	1149	1169	1189

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



# XF 9.7 DC

Matte Carbon Berry

MTB FULL-SUSPENSION / XF TR



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 MTB bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### FRAMESET

FRAME	Carbon MTB DC SU-01.2, Advanced Down Country Geometry, Travel 130 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Dropped seat post ready
SUSPENSION FORK	RockShox PIKE Ultimate Charger 3 RC2, Tapered, DebonAir+, 15x110mm axle, 130mm travel
REAR SHOCK	RockShox Deluxe Ultimate RCT, size 190x45mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1052S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	BOOST UDH LIGHT, SB01-LT, TA12x175.5, M12x1,0x14.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SLX SL-M7100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100, Shadow Plus Design
CRANKSET	SHIMANO XT FC-M8120, Hollowtech II, 34T
CASSETTE	SHIMANO SLX CS-M7101, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO XT M8120, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 180mm
BRAKES REAR	SHIMANO XT M8120, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

### WHEELS

WHEELSET FRONT	DT Swiss M 1900 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss M 1900 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TYRES FRONT	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip
TYRES REAR	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip

### COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 760mm, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

### PARTS

SADDLE	Fizik Ridon X5, Alloy
SEAT POST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

## GEOMETRY

FRAME SIZE	S	M	L	XL
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	583	609	629	649
STACK HEIGHT (mm) ToUpper()	590	600	609	618
REACH (mm) ToUpper()	428	451	469	487
SEAT TUBE ANGLE ToUpper()	75,3°	75,3°	75,3°	75,3°
HEAD TUBE ANGLE ToUpper()	65,6°	65,6°	65,6°	65,6°
REAR CENTER (mm) ToUpper()	430	430	430	430
HEAD TUBE LENGTH (mm) ToUpper()	90	100	110	120
WHEELBASE (mm) ToUpper()	1160	1187	1209	1230

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# XF 9.6 DC

Matte Carbon / Grey

MTB FULL-SUSPENSION / XF TR



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 MTB bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### FRAMESET

FRAME	Carbon MTB DC SU-01.2, Advanced Down Country Geometry, Travel 130 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Dropped seat post ready
SUSPENSION FORK	RockShox PIKE Select Charger RC, Tapered, DebonAir+, 15x110mm axle, 130mm travel
REAR SHOCK	RockShox Deluxe Select+ RT, size 190x45mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1052S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	BOOST UDH LIGHT, SB01-LT, TA12x175.5, M12x1,0x14.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SLX SL-M7100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO SLX RD-M7100, Shadow Plus Design
CRANKSET	SHIMANO SLX FC-M7120, Hollowtech II, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO M6120, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKES REAR	SHIMANO M6120, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 180mm

### WHEELS

WHEELSET FRONT	DT Swiss M 1900 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss M 1900 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TYRES FRONT	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip
TYRES REAR	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip

### COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 760mm, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

### PARTS

SADDLE	Fizik Ridon X5, Alloy
SEAT POST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

## GEOMETRY

FRAME SIZE	S	M	L	XL
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	583	609	629	649
STACK HEIGHT (mm) ToUpper()	590	600	609	618
REACH (mm) ToUpper()	428	451	469	487
SEAT TUBE ANGLE ToUpper()	75,3°	75,3°	75,3°	75,3°
HEAD TUBE ANGLE ToUpper()	65,6°	65,6°	65,6°	65,6°
REAR CENTER (mm) ToUpper()	430	430	430	430
HEAD TUBE LENGTH (mm) ToUpper()	90	100	110	120
WHEELBASE (mm) ToUpper()	1160	1187	1209	1230

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# XF 9.2 DC

Matte Mustard

MTB FULL-SUSPENSION / XF TR



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 MTB bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### FRAMESET

FRAME	Carbon MTB Trail SU-01, Advanced Trail Geometry, Travel 130 mm, Tapered Head Tube, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost 12x148 mm, Inner Cable Routing, dropper seat post ready
SUSPENSION FORK	RockShox 35 Silver TK, Tapered, SoloAir, 15x110mm axle, 130mm travel
REAR SHOCK	AF2 - Twin, LockOut Lever, size 190x51mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-220 R4, ZS44/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	BOOST 411K12C1800114, TA12x171.5, M12xP1.5x15.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	SHIMANO FC-MT510, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKES REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 180mm

### WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIMS FRONT	BLACK JACK Ready 30, Disc, 32H, Tubeless Ready
TYRES FRONT	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12x148mm, THRU Type AXLE
RIMS REAR	BLACK JACK Ready 30, Disc, 32H, Tubeless Ready
TYRES REAR	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Alloy

### COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 760mm, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

### PARTS

SADDLE	Fizi:k Ridon X5, Alloy
SEAT POST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

## GEOMETRY

FRAME SIZE	S	M	L	XL
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	584	610	630	650
STACK HEIGHT (mm) ToUpper()	589	600	608	617
REACH (mm) ToUpper()	407	429	449	465
SEAT TUBE ANGLE toUpper()	74°	74°	74°	74°
HEAD TUBE ANGLE toUpper()	66°	66°	66°	66°
REAR CENTER (mm) ToUpper()	428	428	428	428
HEAD TUBE LENGTH (mm) ToUpper()	90	100	110	120
WHEELBASE (mm) ToUpper()	1154	1180	1200	1220

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



# XF 6.6 DC

Matte Green Grey

MTB FULL-SUSPENSION / XF TR



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 MTB bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### FRAMESET

FRAME	Alu X6 Ultimate MTB Trail SU-02.2, Advanced Geometry Travel 130 mm, Integrated Cable Routing, BB92, 3D alloy one piece link, Alloy swingarm, SR dropout, Boost 12x148 mm, Inner cable routing, Dropped seat post ready.
SUSPENSION FORK	RockShox PIKE Select Charger RC, Tapered, DebonAir+, 15x110mm axle, 130mm travel
REAR SHOCK	RockShox Deluxe Select+ RT, size 190x45mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1052, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	BOOST UDH, 411K12B1800075, TA12x175.5, M12xP1.0x14.5mm, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SLX SL-M7100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100, Shadow Plus Design
CRANKSET	SHIMANO SLX FC-M7120, Hollowtech II, 34T
CASSETTE	SHIMANO SLX CS-M7101, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKES REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 180mm

### WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIMS FRONT	BLACK JACK Ready 30, Disc, 32H, Tubeless Ready
TYRES FRONT	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12x148mm, THRU Type AXLE
RIMS REAR	BLACK JACK Ready 30, Disc, 32H, Tubeless Ready
TYRES REAR	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Alloy

### COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 760mm, 35mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

### PARTS

SADDLE	Fizi:k Ridon X5, Alloy
SEAT POST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

## GEOMETRY

FRAME SIZE	S	M	L	XL
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	368	431	482	533
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	583	609	629	649
STACK HEIGHT (mm) ToUpper()	590	600	609	618
REACH (mm) ToUpper()	428	451	469	487
SEAT TUBE ANGLE ToUpper()	75,3°	75,3°	75,3°	75,3°
HEAD TUBE ANGLE ToUpper()	65,6°	65,6°	65,6°	65,6°
REAR CENTER (mm) ToUpper()	430	430	430	430
HEAD TUBE LENGTH (mm) ToUpper()	90	100	110	120
WHEELBASE (mm) ToUpper()	1160	1187	1209	1230

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# XF 6.2 DC

Gloss Olive

MTB FULL-SUSPENSION / XF TR



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 MTB bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### FRAMESET

FRAME	Alu X6 Ultimate MTB Trail SU-02.2, Advanced Geometry Travel 130 mm, Integrated Cable Routing, BB92, 3D alloy one piece link, Alloy swingarm, SR dropout, Boost 12x148 mm, Inner cable routing, Dropped seat post ready.
SUSPENSION FORK	RockShox 35 Silver TK, Tapered, SoloAir, 15x110mm axle, 130mm travel
REAR SHOCK	RockShox Deluxe Select+ RT, size 190x45mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1052, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	BOOST UDH, 411K12B1800075, TA12x175.5, M12xP1.0x14.5mm, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	SHIMANO FC-MT510, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 180mm
BRAKES REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 180mm

### WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIMS FRONT	BLACK JACK Ready 30, Disc, 32H, Tubeless Ready
TYRES FRONT	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIMS REAR	BLACK JACK Ready 30, Disc, 32H, Tubeless Ready
TYRES REAR	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Alloy

### COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 760mm, 35mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

### PARTS

SADDLE	Fizi:k Ridon X5, Alloy
SEAT POST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

## GEOMETRY

FRAME SIZE	S	M	L	XL
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	368	431	482	533
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	583	609	629	649
STACK HEIGHT (mm) ToUpper()	590	600	609	618
REACH (mm) ToUpper()	428	451	469	487
SEAT TUBE ANGLE ToUpper()	75,3°	75,3°	75,3°	75,3°
HEAD TUBE ANGLE ToUpper()	65,6°	65,6°	65,6°	65,6°
REAR CENTER (mm) ToUpper()	430	430	430	430
HEAD TUBE LENGTH (mm) ToUpper()	90	100	110	120
WHEELBASE (mm) ToUpper()	1160	1187	1209	1230

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# XP 9.8 Team

Gloss Carbon Red / Black

MTB HARDTAIL / TEAM



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 MTB bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### FRAMESET

FRAME	Carbon MTB Race Pro Mid Modulus, Advanced Race Geometry, Integrated Cable Routing, BB92, SR dropout, Boost Thru Axle 148x12 mm
SUSPENSION FORK	DT Swiss F232 ONE, Tapered, 15x110mm axle, 100mm travel
BOTTOM BRACKET	SHIMANO BB-71-41A, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1052S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	BOOST UDH LIGHT, SB01-LT, TA12x175.5, M12x1,0x14.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO XTR SL-M9100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO XTR RD-M9100, Shadow Plus Design
CRANKSET	SHIMANO XTR FC-M9100, Hollowtech II, 34T
CASSETTE	SHIMANO XT CS-M8100, 12-speed, 10-51T
CHAIN	SHIMANO XT CN-M8100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO XTR M9100, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-MT800, 160mm
BRAKES REAR	SHIMANO XTR M9100, hydraulic disc brake
ROTOR REAR	SHIMANO RT-MT800, 160mm

### WHEELS

WHEELSET FRONT	DT Swiss XR 1700 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss XR 1700 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TYRES FRONT	Schwalbe Racing Ray Evo, SuperGround, TL-Easy, 29x2.25", ADDIX SpeedGrip
TYRES REAR	Schwalbe Racing Ralph Evo, SuperGround, TL-Easy, 29x2.25", ADDIX Speed

### COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

### PARTS

SADDLE	Fizik Ridon X3, Kium
SEATPOST	ONE Race, Carbon Ultimate, 27.2mm
SEAT POST CLAMP	ONE CC-080A, 31,8mm, Black

## GEOMETRY

FRAME SIZE	S	M	L	XL
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	590	615	635	645
STACK HEIGHT (mm) ToUpper()	599	603	613	622
REACH (mm) ToUpper()	435	455	475	495
SEAT TUBE ANGLE ToUpper()	75,5°	75,2°	75,4°	76,4°
HEAD TUBE ANGLE ToUpper()	66,5°	66,5°	66,5°	66,5°
REAR CENTER (mm) ToUpper()	430	430	430	430
HEAD TUBE LENGTH (mm) ToUpper()	90	95	105	115
WHEELBASE (mm) ToUpper()	1147	1169	1193	1217

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



# XP 9.5 Team

Gloss Carbon Red / Black

MTB HARDTAIL / TEAM



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 Road Racing bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### FRAMESET

FRAME	Carbon MTB Race Pro Mid Modulus, Advanced Race Geometry, Integrated Cable Routing, BB92, SR dropout, Boost Thru Axle 148x12 mm
SUSPENSION FORK	DT Swiss F232 ONE, Tapered, 15x110mm axle, 100mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1090S ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, STAINLESS BEARINGS, BLACK
REAR AXLE	BOOST UDH LIGHT, SB01-LT, TA12x175.5, M12x1,0x14.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE XT SL-M8100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100, Shadow Plus Design
CRANKSET	SHIMANO XT FC-M8100, Hollowtech II, 34T
CASSETTE	SHIMANO XT CS-M8100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO XT M8100, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-MT800, 160mm
BRAKES REAR	SHIMANO XT M8100, hydraulic disc brake
ROTOR REAR	SHIMANO RT-MT800, 160mm

### WHEELS

WHEELSET FRONT	DT Swiss XR 1700 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss XR 1700 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TYRES FRONT	Schwalbe Racing Ray Performance, TL-Ready, 29x2.25", ADDIX SpeedGrip
TYRES REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 29x2.25", ADDIX

### COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 760mm, 31,8mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

### PARTS

SADDLE	Fizik Ridon X5, Alloy
SEATPOST	ONE Race, Carbon, 27.2mm
SEAT POST CLAMP	ONE CC-080A, 31,8mm, Black

## GEOMETRY

FRAME SIZE	S	M	L	XI
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	590	615	635	645
STACK HEIGHT (mm) ToUpper()	599	603	613	622
REACH (mm) ToUpper()	435	455	475	495
SEAT TUBE ANGLE ToUpper()	75,5°	75,2°	75,4°	76,4°
HEAD TUBE ANGLE ToUpper()	66,5°	66,5°	66,5°	66,5°
REAR CENTER (mm) ToUpper()	430	430	430	430
HEAD TUBE LENGTH (mm) ToUpper()	90	95	105	115
WHEELBASE (mm) ToUpper()	1147	1169	1193	1217

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# XP 9.7

Matte Carbon

MTB HARDTAIL / XP



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 MTB bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### FRAMESET

FRAME	Carbon MTB Race Pro Mid Modulus, Advanced Race Geometry, Integrated Cable Routing, BB92, SR dropout, Boost Thru Axle 148x12 mm
SUSPENSION FORK	DT Swiss F232 ONE, Tapered, 15x110mm axle, 100mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1090S ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, STAINLESS BEARINGS, BLACK
REAR AXLE	BOOST UDH LIGHT, SB01-LT, TA12x175.5, M12x1,0x14.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SLX SL-M7100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100, Shadow Plus Design
CRANKSET	SHIMANO XT FC-M8100, Hollowtech II, 34T
CASSETTE	SHIMANO SLX CS-M7101, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO XT M8100, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 180mm
BRAKES REAR	SHIMANO XT M8100, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 160mm

### WHEELS

WHEELSET FRONT	DT Swiss X 1900 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss X 1900 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TYRES FRONT	Schwalbe Racing Ray Performance, TL-Ready, 29x2.25", ADDIX SpeedGrip
TYRES REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 29x2.25", ADDIX

### COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 760mm, 31,8mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

### PARTS

SADDLE	Fizik Ridon X5, Alloy
SEATPOST	ONE Race, Carbon, 27.2mm
SEAT POST CLAMP	ONE CC-080A, 31,8mm, Black

## GEOMETRY

FRAME SIZE	S	M	L	XI
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	590	615	635	645
STACK HEIGHT (mm) ToUpper()	599	603	613	622
REACH (mm) ToUpper()	435	455	475	495
SEAT TUBE ANGLE ToUpper()	75,5°	75,2°	75,4°	76,4°
HEAD TUBE ANGLE ToUpper()	66,5°	66,5°	66,5°	66,5°
REAR CENTER (mm) ToUpper()	430	430	430	430
HEAD TUBE LENGTH (mm) ToUpper()	90	95	105	115
WHEELBASE (mm) ToUpper()	1147	1169	1193	1217

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# XP 9.6

Gloss Red / Black

MTB HARDTAIL / XP



## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 MTB bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### FRAMESET

FRAME	Carbon MTB Race Pro Mid Modulus, Advanced Race Geometry, Integrated Cable Routing, BB92, SR dropout, Boost Thru Axle 148x12 mm
SUSPENSION FORK	RockShox SID SL RL R, Tapered, DebonAir, 15x110mm axle, 100mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1090S ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, STAINLESS BEARINGS, BLACK
REAR AXLE	BOOST UDH LIGHT, SB01-LT, TA12x175.5, M12x1,0x14.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SLX SL-M7100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO SLX RD-M7100, Shadow Plus Design
CRANKSET	SHIMANO SLX FC-M7100, Hollowtech II, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO M6100, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKES REAR	SHIMANO M6100, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

### WHEELS

WHEELSET FRONT	DT Swiss X 1900 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss X 1900 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TYRES FRONT	Schwalbe Racing Ray Performance, TL-Ready, 29x2.25", ADDIX SpeedGrip
TYRES REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 29x2.25", ADDIX

### COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 760mm, 31,8mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

### PARTS

SADDLE	Fizik Ridon X5, Alloy
SEATPOST	ONE Race, Carbon, 27.2mm
SEAT POST CLAMP	ONE CC-080A, 31,8mm, Black

## GEOMETRY

FRAME SIZE	S	M	L	XI
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	590	615	635	645
STACK HEIGHT (mm) ToUpper()	599	603	613	622
REACH (mm) ToUpper()	435	455	475	495
SEAT TUBE ANGLE ToUpper()	75,5°	75,2°	75,4°	76,4°
HEAD TUBE ANGLE ToUpper()	66,5°	66,5°	66,5°	66,5°
REAR CENTER (mm) ToUpper()	430	430	430	430
HEAD TUBE LENGTH (mm) ToUpper()	90	95	105	115
WHEELBASE (mm) ToUpper()	1147	1169	1193	1217

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



# XP 9.2

Gloss Berry Carbon

MTB HARDTAIL / XP



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 MTB bicycles
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### FRAMESET

FRAME	Carbon MTB Race Pro Mid Modulus, Advanced Race Geometry, Integrated Cable Routing, BB92, SR dropout, Boost Thru Axle 148x12 mm
SUSPENSION FORK	RockShox Recon Silver RL R, Tapered, SoloAir, 15x110mm axle, 100mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1090 ICR, ZS56/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	BOOST UDH, 411K12B1800075, TA12x175.5, M12xP1.0x14.5mm, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	SHIMANO FC-MT510, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKES REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

### WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIMS FRONT	BLACK JACK Ready 25, Disc, 32H, Tubeless Ready
TYRES FRONT	Schwalbe Racing Ray Performance, 29x2.25", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIMS REAR	BLACK JACK Ready 25, Disc, 32H, Tubeless Ready
TYRES REAR	Schwalbe Racing Ray Performance, 29x2.25", ADDIX
SPOKES	SAPIM Laser/Race, Stainless Black
NIPPLES	SAPIM, Alloy

### COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 760mm, 31,8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

### PARTS

SADDLE	Fizik Ridon X5, Alloy
SEATPOST	ONE Race, Alloy, 27.2mm
SEAT POST CLAMP	ONE CC-080A, 31,8mm, Black

## GEOMETRY

FRAME SIZE	S	M	L	XI
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	590	615	635	645
STACK HEIGHT (mm) ToUpper()	599	603	613	622
REACH (mm) ToUpper()	435	455	475	495
SEAT TUBE ANGLE ToUpper()	75,5°	75,2°	75,4°	76,4°
HEAD TUBE ANGLE ToUpper()	66,5°	66,5°	66,5°	66,5°
REAR CENTER (mm) ToUpper()	430	430	430	430
HEAD TUBE LENGTH (mm) ToUpper()	90	95	105	115
WHEELBASE (mm) ToUpper()	1147	1169	1193	1217

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# X-ROAD 9.8 GF

Gloss Red Carbon

ROAD & GRAVEL / GRAN FONDO



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 Road Racing bicycles
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### FRAMESET

FRAME	Carbon X-Road Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready.
FORK	X-ROAD Carbon Fork
BOTTOM BRACKET	SHIMANO BB-72-41B, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-525S, ICR, OD56, IS52/28.6 - 40IPS, Stainless Bearings
FRONT AXLE	NON BOOST LITE SB02-LT, TA12x125, M12xP1.5x10L, Black
REAR AXLE	NON BOOST LITE, SB02-LT, TA12x165, M12xP1.5x14L, Black

### DRIVETRAIN

SHIFTERS LEFT	SHIMANO ULTEGRA R8170, Di2, 2-speed
SHIFTERS RIGHT	SHIMANO ULTEGRA R8170, Di2, 12-speed
FRONT DERAILLEUR	SHIMANO ULTEGRA FD-R8150, Down Swing, Brazed-On Type
REAR DERAILLEUR	SHIMANO ULTEGRA RD-R8150, Shadow Design
CRANKSET	SHIMANO ULTEGRA FC-R8100, Hollowtech II, 50-34T
CASSETTE	SHIMANO ULTEGRA CS-R8101, 12-speed, 11-34T
CHAIN	SHIMANO XT CN-M8100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO ULTEGRA R8170, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-MT800, 140mm
BRAKES REAR	SHIMANO ULTEGRA R8170, hydraulic disc brake
ROTOR REAR	SHIMANO RT-MT800, 140mm

### WHEELS

WHEELSET FRONT	DT Swiss ERC 1400 DICUT®, Carbon, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss ERC 1400 DICUT®, Carbon, CL, 12x142mm, SH11, Tubeless Ready
TYRES FRONT	Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race
TYRES REAR	Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race

### COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Handlebar Tape

### PARTS

SADDLE	Fizik Antares R1, Carbon
SEATPOST	ONE Aero Carbon
SEAT POST CLAMP	Frame Integrated Clamp

## GEOMETRY

FRAME SIZE	S	M	L	XL
WHEEL SIZE ToUpper()	700c	700c	700c	700c
SEAT TUBE LENGTH (mm) ToUpper()	462	482	502	522
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	532	545	569	590,6
STACK HEIGHT (mm) ToUpper()	537	557	578	597,2
REACH (mm) ToUpper()	376	380	392	408
SEAT TUBE ANGLE ToUpper()	73,8°	73,5°	73°	73°
HEAD TUBE ANGLE ToUpper()	71°	71,5°	72°	72°
REAR CENTER (mm) ToUpper()	406	406	406	406
HEAD TUBE LENGTH (mm) ToUpper()	120	140	160	180
WHEELBASE (mm) ToUpper()	990	996	1010	1032,6

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# X-ROAD 9.7 GF

Matte Carbon

ROAD & GRAVEL / GRAN FONDO



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 Road Racing bicycles
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### FRAMESET

FRAME	Carbon X-Road Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready.
FORK	X-ROAD Carbon Fork
BOTTOM BRACKET	SHIMANO BB-72-41B, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-525S, ICR, OD56, IS52/28.6 - 40IPS, Stainless Bearings
FRONT AXLE	NON BOOST LITE SB02-LT, TA12x125, M12xP1.5x10L, Black
REAR AXLE	NON BOOST LITE, SB02-LT, TA12x165, M12xP1.5x14L, Black

### DRIVETRAIN

SHIFTERS LEFT	SHIMANO ULTEGRA R8170, Di2, 2-speed
SHIFTERS RIGHT	SHIMANO ULTEGRA R8170, Di2, 12-speed
FRONT DERAILLEUR	SHIMANO ULTEGRA FD-R8150, Down Swing, Brazed-On Type
REAR DERAILLEUR	SHIMANO ULTEGRA RD-R8150, Shadow Design
CRANKSET	SHIMANO ULTEGRA FC-R8100, Hollowtech II, 50-34T
CASSETTE	SHIMANO ULTEGRA CS-R8101, 12-speed, 11-34T
CHAIN	SHIMANO XT CN-M8100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO ULTEGRA R8170, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-MT800, 140mm
BRAKES REAR	SHIMANO ULTEGRA R8170, hydraulic disc brake
ROTOR REAR	SHIMANO RT-MT800, 140mm

### WHEELS

WHEELSET FRONT	DT Swiss ER 1600 SPLINE®, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss ER 1600 SPLINE®, CL, 12x142mm, SH11, Tubeless Ready
TYRES FRONT	Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race
TYRES REAR	Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race

### COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Handlebar Tape

### PARTS

SADDLE	Fizik Vento Argo R5, Alloy
SEATPOST	ONE Aero Carbon
SEAT POST CLAMP	Frame Integrated Clamp

## GEOMETRY

FRAME SIZE	S	M	L	XI
WHEEL SIZE ToUpper()	700c	700c	700c	700c
SEAT TUBE LENGTH (mm) ToUpper()	462	482	502	522
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	532	545	569	590,6
STACK HEIGHT (mm) ToUpper()	537	557	578	597,2
REACH (mm) ToUpper()	376	380	392	408
SEAT TUBE ANGLE ToUpper()	73,8°	73,5°	73°	73°
HEAD TUBE ANGLE ToUpper()	71°	71,5°	72°	72°
REAR CENTER (mm) ToUpper()	406	406	406	406
HEAD TUBE LENGTH (mm) ToUpper()	120	140	160	180
WHEELBASE (mm) ToUpper()	990	996	1010	1032,6

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# X-ROAD 9.5 GF

Gloss Grey / Orange Red

ROAD & GRAVEL / GRAN FONDO



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 Road Racing bicycles
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### FRAMESET

FRAME	Carbon X-Road Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready.
FORK	X-ROAD Carbon Fork
BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	NON BOOST LITE SB02-LT, TA12x125, M12xP1.5x10L, Black
REAR AXLE	NON BOOST LITE, SB02-LT, TA12x165, M12xP1.5x14L, Black

### DRIVETRAIN

SHIFTERS LEFT	SHIMANO 105 R7170, Di2, 2-speed
SHIFTERS RIGHT	SHIMANO 105 R7170, Di2, 12-speed
FRONT DERAILLEUR	SHIMANO 105 FD-R7150, Down Swing, Brazed-On Type
REAR DERAILLEUR	SHIMANO 105 RD-R7150, Shadow Design
CRANKSET	SHIMANO 105 FC-R7100, Hollowtech II, 50-34T
CASSETTE	SHIMANO 105 CS-R7100, 12 speed, 11-34T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO 105 R7170, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 140mm
BRAKES REAR	SHIMANO 105 R7170, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

### WHEELS

WHEELSET FRONT	DT Swiss C 1800 SPLINE®, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss C 1800 SPLINE®, CL, 12x142mm, SH11, Tubeless Ready
TYRES FRONT	Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race
TYRES REAR	Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race

### COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm
GRIPS LEFT	ONE Handlebar Tape

### PARTS

SADDLE	Selle Royal Gravel
SEATPOST	ONE Aero Carbon
SEAT POST CLAMP	Frame Integrated Clamp

## GEOMETRY

FRAME SIZE	S	M	L	XL
WHEEL SIZE ToUpper()	700c	700c	700c	700c
SEAT TUBE LENGTH (mm) ToUpper()	462	482	502	522
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	532	545	569	590,6
STACK HEIGHT (mm) ToUpper()	537	557	578	597,2
REACH (mm) ToUpper()	376	380	392	408
SEAT TUBE ANGLE ToUpper()	73,8°	73,5°	73°	73°
HEAD TUBE ANGLE ToUpper()	71°	71,5°	72°	72°
REAR CENTER (mm) ToUpper()	406	406	406	406
HEAD TUBE LENGTH (mm) ToUpper()	120	140	160	180
WHEELBASE (mm) ToUpper()	990	996	1010	1032,6

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



# X-ROAD 9.3 GF

Matte Carbon / White

ROAD & GRAVEL / GRAN FONDO



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 Road Racing bicycles
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### FRAMESET

FRAME	Carbon X-Road Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready.
FORK	X-ROAD Carbon Fork
BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	NON BOOST 411K12C1400047, TA12x125, M12xP1.5x10L, Black
REAR AXLE	NON BOOST 411K12C1800115, TA12x165, M12xP1.5x14L, Black

### DRIVETRAIN

SHIFTERS LEFT	SHIMANO 105 R7120, 2-speed
SHIFTERS RIGHT	SHIMANO 105 R7120, 12-speed
FRONT DERAILLEUR	SHIMANO 105 FD-R7100, Down Swing, Down Pull, Brazed-On Type
REAR DERAILLEUR	SHIMANO 105 RD-R7100, Shadow Design
CRANKSET	SHIMANO 105 FC-R7100, Hollowtech II, 50-34T
CASSETTE	SHIMANO 105 CS-R7100, 12 speed, 11-34T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO 105 R7120, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 140mm
BRAKES REAR	SHIMANO 105 R7120, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

### WHEELS

WHEELSET FRONT	DT Swiss C 1800 SPLINE®, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss C 1800 SPLINE®, CL, 12x142mm, SH11, Tubeless Ready
TYRES FRONT	Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race
TYRES REAR	Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race

### COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm
GRIPS LEFT	ONE Handlebar Tape

### PARTS

SADDLE	Selle Royal Gravel
SEATPOST	ONE Aero Carbon
SEAT POST CLAMP	Frame Integrated Clamp

## GEOMETRY

FRAME SIZE	S	M	L	XL
WHEEL SIZE ToUpper()	700c	700c	700c	700c
SEAT TUBE LENGTH (mm) ToUpper()	462	482	502	522
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	532	545	569	590,6
STACK HEIGHT (mm) ToUpper()	537	557	578	597,2
REACH (mm) ToUpper()	376	380	392	408
SEAT TUBE ANGLE ToUpper()	73,8°	73,5°	73°	73°
HEAD TUBE ANGLE ToUpper()	71°	71,5°	72°	72°
REAR CENTER (mm) ToUpper()	406	406	406	406
HEAD TUBE LENGTH (mm) ToUpper()	120	140	160	180
WHEELBASE (mm) ToUpper()	990	996	1010	1032,6

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# X-ROAD 6.5 GF

Matte Black Stealth

ROAD & GRAVEL / GRAN FONDO



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 Road Racing bicycles
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### FRAMESET

FRAME	Alu X6 Ultralite X-Road Race , Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, SH dropout, Integrated Cable Routing, Full Carbon front fork; mudguards ready
FORK	X-ROAD Carbon Fork
BOTTOM BRACKET	SHIMANO BB-R60, BSA, shell 68mm
HEADSET	ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	NON BOOST 411K12C1400047, TA12x125, M12xP1.5x10L, Black
REAR AXLE	NON BOOST 411K12C1800115, TA12x165, M12xP1.5x14L, Black

### DRIVETRAIN

SHIFTERS LEFT	SHIMANO 105 R7120, 2-speed
FRONT DERAILLEUR	SHIMANO 105 FD-R7100, Down Swing, Down Pull, Brazed-On Type
REAR DERAILLEUR	SHIMANO 105 RD-R7100, Shadow Design
CRANKSET	SHIMANO 105 FC-R7100, Hollowtech II, 50-34T
CASSETTE	SHIMANO 105 CS-R7100, 12 speed, 11-34T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO 105 R7120, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 140mm
BRAKES REAR	SHIMANO 105 R7120, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

### WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIMS FRONT	DT Swiss R500, Disc, 28H, Tubeless Ready
TYRES FRONT	Schwalbe One Performance, RaceGuard, 30-622, ADDIX
HUB REAR	SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE
RIMS REAR	DT Swiss R500, Disc, 28H, Tubeless Ready
TYRES REAR	Schwalbe One Performance, RaceGuard, 30-622, ADDIX
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Alloy

### COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm
GRIPS LEFT	ONE Handlebar Tape

### PARTS

SADDLE	Selle Royal Gravel
SEATPOST	ONE Race, Alloy, 27.2mm
SEAT POST CLAMP	ONE CC-080A, 31,8mm, Black

## GEOMETRY

FRAME SIZE	Xs	S	M	L	XI
WHEEL SIZE ToUpper()	700c	700c	700c	700c	700c
SEAT TUBE LENGTH (mm) ToUpper()	470	490	510	530	550
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	523	530	540	570	590
STACK HEIGHT (mm) ToUpper()	549	558	569	606	616
REACH (mm) ToUpper()	368	367	371	384	401
SEAT TUBE ANGLE ToUpper()	74,3°	73,8°	73,5°	73°	73°
HEAD TUBE ANGLE ToUpper()	71,5°	71,5°	72°	73°	73°
REAR CENTER (mm) ToUpper()	414	414	414	414	414
HEAD TUBE LENGTH (mm) ToUpper()	125	135	145	180	190
WHEELBASE (mm) ToUpper()	949	992	990	1010	1029,8

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# X-ROAD 6.3 GF

Gloss Grey / Black

ROAD & GRAVEL / GRAN FONDO



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 Road Racing bicycles
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### FRAMESET

FRAME	Alu X6 Ultralite X-Road Race, Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, SH dropout, Integrated Cable Routing, Full Carbon front fork; mudguards ready
FORK	X-ROAD Carbon Fork
BOTTOM BRACKET	SHIMANO, Cartridge Bearing
HEADSET	ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	NON BOOST 411K12C1400047, TA12x125, M12xP1.5x10L, Black
REAR AXLE	NON BOOST 411K12C1800115, TA12x165, M12xP1.5x14L, Black

### DRIVETRAIN

SHIFTERS LEFT	SHIMANO TIAGRA R-4720, 2-speed
SHIFTERS RIGHT	SHIMANO TIAGRA R-4720, 10-speed
FRONT DERAILLEUR	SHIMANO TIAGRA FD-4700, Brazed-On Type
REAR DERAILLEUR	SHIMANO TIAGRA RD-4700
CRANKSET	SHIMANO FC-RS400, 50-34T
CASSETTE	SHIMANO CS-HG500, 10-speed, 11-34T
CHAIN	KMC X10

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO TIAGRA R-4720, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 140mm
BRAKES REAR	SHIMANO TIAGRA R4720, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

### WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIMS FRONT	STARS J22GT, Disc, 28H
TYRES FRONT	Schwalbe Lugano II, KevlarGuard, 32-622
HUB REAR	SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE
RIMS REAR	STARS J22GT, Disc, 28H
TYRES REAR	Schwalbe Lugano II, KevlarGuard, 32-622
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Brass

### COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm
GRIPS LEFT	ONE Handlebar Tape

### PARTS

SADDLE	Selle Royal Gravel
SEATPOST	ONE Race, Alloy, 27.2mm
SEAT POST CLAMP	ONE CC-080A, 31,8mm, Black

## GEOMETRY

FRAME SIZE	Xs	S	M	L	XI
WHEEL SIZE ToUpper()	700c	700c	700c	700c	700c
SEAT TUBE LENGTH (mm) ToUpper()	470	490	510	530	550
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	523	530	540	570	590
STACK HEIGHT (mm) ToUpper()	549	558	569	606	616
REACH (mm) ToUpper()	368	367	371	384	401
SEAT TUBE ANGLE ToUpper()	74,3°	73,8°	73,5°	73°	73°
HEAD TUBE ANGLE ToUpper()	71,5°	71,5°	72°	73°	73°
REAR CENTER (mm) ToUpper()	414	414	414	414	414
HEAD TUBE LENGTH (mm) ToUpper()	125	135	145	180	190
WHEELBASE (mm) ToUpper()	949	992	990	1010	1029,8

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# X-ROAD 9.7 GR

Matte Carbon Berry

ROAD & GRAVEL / GRAVEL



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 Road Racing bicycles
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### FRAMESET

FRAME	Carbon X-Road Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready.
FORK	X-ROAD Carbon Fork
BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-525S, ICR, OD56, IS52/28.6 - 40IPS, Stainless Bearings
FRONT AXLE	NON BOOST LITE SB02-LT, TA12x125, M12xP1.5x10L, Black
REAR AXLE	NON BOOST LITE, SB02-LT, TA12x165, M12xP1.5x14L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO GRX RX820, 12-speed
REAR DERAILLEUR	SHIMANO GRX RD-RX822, Shadow Plus Design
CRANKSET	SHIMANO GRX FC-RX820, Hollowtech II, 42T
CASSETTE	SHIMANO XT CS-M8100, 12-speed, 10-45T
CHAIN	SHIMANO XT CN-M8100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO GRX RX820, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-MT800, 160mm
BRAKES REAR	SHIMANO GRX RX820, hydraulic disc brake
ROTOR REAR	SHIMANO RT-MT800, 140mm

### WHEELS

WHEELSET FRONT	DT Swiss GR 1600 SPLINE®, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss GR 1600 SPLINE®, CL, 12x142mm, SH12, Tubeless Ready
TYRES FRONT	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX
TYRES REAR	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX

### COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Handlebar Tape

### PARTS

SADDLE	Fizik Vento Argo R5, Alloy
SEATPOST	ONE Aero Carbon
SEAT POST CLAMP	Frame Integrated Clamp

## GEOMETRY

FRAME SIZE	S	M	L	XL
WHEEL SIZE ToUpper()	700c	700c	700c	700c
SEAT TUBE LENGTH (mm) ToUpper()	462	482	502	522
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	532	545	569	590,6
STACK HEIGHT (mm) ToUpper()	537	557	578	597,2
REACH (mm) ToUpper()	376	380	392	408
SEAT TUBE ANGLE ToUpper()	73,8°	73,5°	73°	73°
HEAD TUBE ANGLE ToUpper()	71°	71,5°	72°	72°
REAR CENTER (mm) ToUpper()	406	406	406	406
HEAD TUBE LENGTH (mm) ToUpper()	120	140	160	180
WHEELBASE (mm) ToUpper()	990	996	1010	1032,6

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



# X-ROAD 9.5 GR

Matte Carbon / Green Grey

ROAD & GRAVEL / GRAVEL



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 Road Racing bicycles
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### FRAMESET

FRAME	Carbon X-Road Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready.
FORK	X-ROAD Carbon Fork
BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	NON BOOST 411K12C1400047, TA12x125, M12xP1.5x10L, Black
REAR AXLE	NON BOOST 411K12C1800115, TA12x165, M12xP1.5x14L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO GRX RX610, 12-speed
REAR DERAILLEUR	SHIMANO GRX RD-RX822, Shadow Plus Design
CRANKSET	SHIMANO GRX FC-RX610, 40T
CASSETTE	SHIMANO SLX CS-M7101, 12-speed, 10-45T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO GRX RX610, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 160mm
BRAKES REAR	SHIMANO GRX RX610, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

### WHEELS

WHEELSET FRONT	DT Swiss G 1800 SPLINE®, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss G 1800 SPLINE®, CL, 12x142mm, SH12, Tubeless Ready
TYRES FRONT	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX
TYRES REAR	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX

### COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm
GRIPS LEFT	ONE Handlebar Tape

### PARTS

SADDLE	Selle Royal Gravel
SEATPOST	ONE Aero Carbon
SEAT POST CLAMP	Frame Integrated Clamp

## GEOMETRY

FRAME SIZE	S	M	L	XL
WHEEL SIZE ToUpper()	700c	700c	700c	700c
SEAT TUBE LENGTH (mm) ToUpper()	462	482	502	522
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	532	545	569	590,6
STACK HEIGHT (mm) ToUpper()	537	557	578	597,2
REACH (mm) ToUpper()	376	380	392	408
SEAT TUBE ANGLE ToUpper()	73,8°	73,5°	73°	73°
HEAD TUBE ANGLE ToUpper()	71°	71,5°	72°	72°
REAR CENTER (mm) ToUpper()	406	406	406	406
HEAD TUBE LENGTH (mm) ToUpper()	120	140	160	180
WHEELBASE (mm) ToUpper()	990	996	1010	1032,6

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# X-ROAD 6.5 GR

Matte Mustard / Black

ROAD & GRAVEL / GRAVEL



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 Road Racing bicycles
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### FRAMESET

FRAME	Alu X6 Ultralite X-Road Race, Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, SH dropout, Integrated Cable Routing, Full Carbon front fork; mudguards ready
FORK	X-ROAD Carbon Fork
BOTTOM BRACKET	SHIMANO, Cartridge Bearing
HEADSET	ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	NON BOOST 411K12C1400047, TA12x125, M12xP1.5x10L, Black
REAR AXLE	NON BOOST 411K12C1800115, TA12x165, M12xP1.5x14L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO GRX RX610, 12-speed
REAR DERAILLEUR	SHIMANO GRX RD-RX822, Shadow Plus Design
CRANKSET	SHIMANO GRX FC-RX610, 40T
CASSETTE	SHIMANO SLX CS-M7101, 12-speed, 10-45T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO GRX RX610, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 160mm
BRAKES REAR	SHIMANO GRX RX610, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

### WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIMS FRONT	DT Swiss R500, Disc, 28H, Tubeless Ready
TYRES FRONT	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX
HUB REAR	SHIMANO FH-MT410, 28H, CL, 12x142mm, THRU Type AXLE
RIMS REAR	DT Swiss R500, Disc, 28H, Tubeless Ready
TYRES REAR	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Brass

### COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm
GRIPS LEFT	ONE Handlebar Tape

### PARTS

SADDLE	Selle Royal Gravel
SEATPOST	ONE Race, Alloy, 27.2mm
SEAT POST CLAMP	ONE CC-080A, 31,8mm, Black

## GEOMETRY

FRAME SIZE	Xs	S	M	L	XI
WHEEL SIZE ToUpper()	700c	700c	700c	700c	700c
SEAT TUBE LENGTH (mm) ToUpper()	470	490	510	530	550
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	523	530	540	570	590
STACK HEIGHT (mm) ToUpper()	549	558	569	606	616
REACH (mm) ToUpper()	368	367	371	384	401
SEAT TUBE ANGLE ToUpper()	74,3°	73,8°	73,5°	73°	73°
HEAD TUBE ANGLE ToUpper()	71,5°	71,5°	72°	73°	73°
REAR CENTER (mm) ToUpper()	414	414	414	414	414
HEAD TUBE LENGTH (mm) ToUpper()	125	135	145	180	190
WHEELBASE (mm) ToUpper()	949	992	990	1010	1029,8

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# X-ROAD 6.3 GR

Matte Green Grey / Black

ROAD & GRAVEL / GRAVEL



COMPUTER VISUALIZATION

## SPECIFICATIONS

### ISO AND ASTM NORM

ISO norm	ISO 4210-2 Road Racing bicycles
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### FRAMESET

FRAME	Alu X6 Ultralite X-Road Race, Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, SH dropout, Integrated Cable Routing, Full Carbon front fork; mudguards ready
FORK	X-ROAD Carbon Fork
BOTTOM BRACKET	SHIMANO, Cartridge Bearing
HEADSET	ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	NON BOOST 411K12C1400047, TA12x125, M12xP1.5x10L, Black
REAR AXLE	NON BOOST 411K12C1800115, TA12x165, M12xP1.5x14L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO GRX RX400, 10-speed
REAR DERAILLEUR	SHIMANO GRX RD-RX400, Shadow Plus Design
CRANKSET	SHIMANO GRX FC-RX600, 40T
CASSETTE	SHIMANO CS-HG500, 10-speed, 11-36T
CHAIN	KMC X10

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO GRX RX400, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 160mm
BRAKES REAR	SHIMANO GRX RX400, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

### WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIMS FRONT	STARS J22GT, Disc, 28H
TYRES FRONT	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX
HUB REAR	SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE
RIMS REAR	STARS J22GT, Disc, 28H
TYRES REAR	Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Brass

### COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm
GRIPS LEFT	ONE Handlebar Tape

### PARTS

SADDLE	Selle Royal Gravel
SEAT POST	ONE Race, Alloy, 27.2mm
SEAT POST CLAMP	ONE CC-080A, 31,8mm, Black

## GEOMETRY

FRAME SIZE	Xs	S	M	L	XI
WHEEL SIZE ToUpper()	700c	700c	700c	700c	700c
SEAT TUBE LENGTH (mm) ToUpper()	470	490	510	530	550
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	523	530	540	570	590
STACK HEIGHT (mm) ToUpper()	549	558	569	606	616
REACH (mm) ToUpper()	368	367	371	384	401
SEAT TUBE ANGLE ToUpper()	74,3°	73,8°	73,5°	73°	73°
HEAD TUBE ANGLE ToUpper()	71,5°	71,5°	72°	73°	73°
REAR CENTER (mm) ToUpper()	414	414	414	414	414
HEAD TUBE LENGTH (mm) ToUpper()	125	135	145	180	190
WHEELBASE (mm) ToUpper()	949	992	990	1010	1029,8

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# eXF 6.8

Gloss Olive Metallic / Black

eMTB FULL SUSPENSION / eXF



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

ESYSTEM	BOSCH CX Performance, Battery PowerTube 750Wh
DISTANCE	200km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 4 For rough Off-Road riding and jumps less than 122cm (48")

### E- BIKE PARTS

MOTOR	BOSCH Performance Line CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 750Wh
DISPLAY	BOSCH Mini Remote

### FRAMESET

FRAME	Alu X6 Ultralite MTB Trail SUE03.1, Advanced e-MTB Geometry, Travel 160 mm, BOSCH CX Performance 5G ready, Integrated 750Wh battery, 3D alloy one piece link, Alloy swingarm, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	DT Swiss F535 ONE, Tapered, 15x110mm axle, 160mm travel
REAR SHOCK	DT Swiss R535 ONE, size 230x65mm
HEADSET	ACROS AZX-1051S, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°, Stainless Bearings
REAR AXLE	BOOST UDH, TA12x171.5, M12xP1.0x14.5mm, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE XT SL-M8100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO XT M8120, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-MT800, 203mm
BRAKES REAR	SHIMANO XT M8120, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO RT-MT800, 180mm

### WHEELS

WHEELSET FRONT	DT Swiss H 1900 SPLINE@, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss H 1900 SPLINE@, CL, 12x148mm, SH12, Tubeless Ready
TYRES FRONT	Schwalbe Nobby Nic Evo, SuperTrail, TL-Easy, 29x2.60", ADDIX Soft
TYRES REAR	Schwalbe Nobby Nic Evo, SuperTrail, TL-Easy, 29x2.60", ADDIX SpeedGrip

### COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 760mm, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

### PARTS

SADDLE	Fizi:k Aidon X5, Alloy
SEAT POST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

## GEOMETRY

FRAME SIZE	S	M	L	XL
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	420	440	490
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	598	610	630	650
STACK HEIGHT (mm) ToUpper()	625	625	625	625
REACH (mm) ToUpper()	465	465	485	505
SEAT TUBE ANGLE ToUpper()	78°	77°	77°	77°
HEAD TUBE ANGLE ToUpper()	64°	64°	64°	64°
REAR CENTER (mm) ToUpper()				
HEAD TUBE LENGTH (mm) ToUpper()	120	120	120	120
WHEELBASE (mm) ToUpper()	1251	1251	1271	1291

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



# eXF 6.5

Gloss Copper / Black

eMTB FULL SUSPENSION / eXF



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

ESYSTEM	BOSCH CX Performance, Battery PowerTube 750Wh
DISTANCE	200km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 4 For rough Off-Road riding and jumps less than 122cm (48")

### E- BIKE PARTS

MOTOR	BOSCH Performance Line CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 750Wh
DISPLAY	BOSCH Mini Remote

### FRAMESET

FRAME	Alu X6 Ultralite MTB Trail SUE03.1, Advanced e-MTB Geometry, Travel 160 mm, BOSCH CX Performance 5G ready, Integrated 750Wh battery, 3D alloy one piece link, Alloy swingarm, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	RockShox 35 Silver TK, Tapered, SoloAir, 15x110mm axle, 160mm travel
REAR SHOCK	RockShox Super Deluxe Select R, size 230x65mm
HEADSET	ACROS AZX-1051S, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°, Stainless Bearings
REAR AXLE	BOOST UDH, TA12x171.5, M12xP1.0x14.5mm, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 203MM
BRAKES REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

### WHEELS

HUB FRONT	SHIMANO HB-MT410-B, 32H, CL, 15x110mm, THRU Type AXLE
RIMS FRONT	STARS J30D, Disc, 32H
TYRES FRONT	Schwalbe Nobby Nic Performance, 29x2.60", ADDIX
HUB REAR	SHIMANO FH-MT410-B, 32H, CL, 12x148mm, THRU Type AXLE
RIMS REAR	STARS J30D, Disc, 32H
TYRES REAR	Schwalbe Nobby Nic Performance, 29x2.60", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

### COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 760mm, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

### PARTS

SADDLE	Fizi:k Aidon X5, Alloy
SEAT POST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

## GEOMETRY

FRAME SIZE	S	M	L	XI
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	420	440	490
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	598	610	630	650
STACK HEIGHT (mm) ToUpper()	625	625	625	625
REACH (mm) ToUpper()	465	465	485	505
SEAT TUBE ANGLE ToUpper()	78°	77°	77°	77°
HEAD TUBE ANGLE ToUpper()	64°	64°	64°	64°
REAR CENTER (mm) ToUpper()				
HEAD TUBE LENGTH (mm) ToUpper()	120	120	120	120
WHEELBASE (mm) ToUpper()	1251	1251	1271	1291

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# eXF 6.2

Gloss Grey / Black

eMTB FULL SUSPENSION / eXF



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 625Wh
DISTANCE	150km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 4 For rough Off-Road riding and jumps less than 122cm (48")

### E- BIKE PARTS

MOTOR	BOSCH Performance Line CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 625Wh
DISPLAY	BOSCH Mini Remote

### FRAMESET

FRAME	Alu X6 Ultralite MTB Trail SUE03.1, Advanced e-MTB Geometry, Travel 160 mm, BOSCH CX Performance 5G ready, Integrated 750Wh battery, 3D alloy one piece link, Alloy swingarm, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	RockShox 35 Silver TK, Tapered, SoloAir, 15x110mm axle, 160mm travel
REAR SHOCK	RockShox Deluxe Select R, size 230x65mm
HEADSET	ACROS AZX-1051, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	BOOST UDH, TA12x171.5, M12xP1.0x14.5mm, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 203MM
BRAKES REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

### WHEELS

HUB FRONT	SHIMANO HB-MT410-B, 32H, CL, 15x110mm, THRU Type AXLE
RIMS FRONT	STARS J30D, Disc, 32H
TYRES FRONT	Schwalbe Nobby Nic Performance, 29x2.60
HUB REAR	SHIMANO FH-MT410-B, 32H, CL, 12x148mm, THRU Type AXLE
RIMS REAR	STARS J30D, Disc, 32H
TYRES REAR	Schwalbe Nobby Nic Performance, 29x2.60
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

### COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 760mm, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

### PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Race, Alloy, 30,9mm
SEAT POST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black

## GEOMETRY

FRAME SIZE	S	M	L	XI
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	420	440	490
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	598	610	630	650
STACK HEIGHT (mm) ToUpper()	625	625	625	625
REACH (mm) ToUpper()	465	465	485	505
SEAT TUBE ANGLE ToUpper()	78°	77°	77°	77°
HEAD TUBE ANGLE ToUpper()	64°	64°	64°	64°
REAR CENTER (mm) ToUpper()				
HEAD TUBE LENGTH (mm) ToUpper()	120	120	120	120
WHEELBASE (mm) ToUpper()	1251	1251	1271	1291

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# eXF 6.2 SUV

Gloss Black / Black

eMTB FULL SUSPENSION / eXF



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

ESYSTEM	BOSCH CX Performance, Battery PowerTube 625Wh
DISTANCE	150km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### E- BIKE PARTS

MOTOR	BOSCH Performance Line CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 625Wh
DISPLAY	BOSCH Kiox 300

### FRAMESET

FRAME	Alu X6 Ultralite MTB Trail SUE03.1, Advanced e-MTB Geometry, Travel 160 mm, BOSCH CX Performance 5G ready, Integrated 750Wh battery, 3D alloy one piece link, Alloy swingarm, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	RockShox 35 Silver TK, Tapered, SoloAir, 15x110mm axle, 140mm travel
REAR SHOCK	RockShox Deluxe Select R, size 230x57.5mm
HEADSET	ACROS AZX-1051, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	BOOST UDH, TA12x171.5, M12xP1.0x14.5mm, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 203MM
BRAKES REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

### WHEELS

HUB FRONT	SHIMANO HB-MT410-B, 32H, CL, 15x110mm, THRU Type AXLE
RIMS FRONT	STARS J30D, Disc, 32H
TYRES FRONT	Schwalbe Johnny Watts Performance, RaceGuard, 29x2.35", ADDIX
HUB REAR	SHIMANO FH-MT410-B, 32H, CL, 12x148mm, THRU Type AXLE
RIMS REAR	STARS J30D, Disc, 32H
TYRES REAR	Schwalbe Johnny Watts Performance, RaceGuard, 29x2.35", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

### COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, 0°
HANDLEBAR	ONE Alloy, 20mm rise, 760mm, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

### PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Race, Alloy, 30,9mm
SEAT POST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black

### CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	AXA Juno
FENDER	Alloy

## GEOMETRY

FRAME SIZE	S	M	L	XI
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	420	440	490
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	598	610	630	650
STACK HEIGHT (mm) ToUpper()	625	625	625	625
REACH (mm) ToUpper()	465	465	485	505
SEAT TUBE ANGLE ToUpper()	78°	77°	77°	77°
HEAD TUBE ANGLE ToUpper()	64°	64°	64°	64°
REAR CENTER (mm) ToUpper()				
HEAD TUBE LENGTH (mm) ToUpper()	120	120	120	120
WHEELBASE (mm) ToUpper()	1251	1251	1271	1291

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# eXC 6.3

Matte Green Grey

eMTB HARDTAIL / eXC



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

ESYSTEM	BOSCH Performance, Battery PowerTube 625Wh
DISTANCE	150km
MAX. TORQUE	75Nm / 300%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### E- BIKE PARTS

MOTOR	BOSCH Performance Line, 65Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 625Wh
DISPLAY	BOSCH Intuvia 100

### FRAMESET

FRAME	Alu 6061 T6, Sport eMTB Geometry, Smooth Welding, Bosch system Powertube 625Wh battery ready, Inner Cable Routing
SUSPENSION FORK	RST Blade, 1.5", 15x100mm axle, 100mm travel
HEADSET	ACROS AZF-604, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	BOOST 411K12C1800114, TA12x171.5, M12xP1.5x15.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO CUES RD-U8000, Shadow Plus Design
CRANKSET	ONE Sport, Alloy
CHAINRING	ONE Sport, 38T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	SHIMANO CN-LG500

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKES REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

### WHEELS

HUB FRONT	SHIMANO HB-MT410-B, 32H, CL, 15x110mm, THRU Type AXLE
RIMS FRONT	STARS J30D, Disc, 32H
TYRES FRONT	Schwalbe Hurricane Performance, 29x2.25, ADDIX
HUB REAR	SHIMANO FH-MT400-B, 32H, CL, 12x148mm, THRU Type AXLE
RIMS REAR	STARS J30D, Disc, 32H
TYRES REAR	Schwalbe Hurricane Performance, 29x2.25, ADDIX
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

### COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, Adjustable
HANDLEBAR	ONE Alloy, 25mm rise, 720mm, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

### PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEAT POST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	Marwi SP-610

## GEOMETRY

FRAME SIZE	S	M	L	XI
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	406	457	510	559
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	570	590	610	630
STACK HEIGHT (mm) ToUpper()	643	652	662	671
REACH (mm) ToUpper()	382	399	420	440
SEAT TUBE ANGLE ToUpper()	73,7°	73,7°	74°	74,2°
HEAD TUBE ANGLE ToUpper()	67°	67°	67°	67°
REAR CENTER (mm) ToUpper()				
HEAD TUBE LENGTH (mm) ToUpper()	130	140	150	160
WHEELBASE (mm) ToUpper()	1176	1197	1222	1243

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



# eXC 6.3

Matte Soft Pink

eMTB HARDTAIL / eXC



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

ESYSTEM	BOSCH Performance, Battery PowerTube 625Wh
DISTANCE	150km
MAX. TORQUE	75Nm / 300%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### E- BIKE PARTS

MOTOR	BOSCH Performance Line, 65Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 625Wh
DISPLAY	BOSCH Intuvia 100

### FRAMESET

FRAME	Alu 6061 T6, Sport eMTB Geometry, Smooth Welding, Bosch system Powertube 625Wh battery ready, Inner Cable Routing
SUSPENSION FORK	RST Blade, 1.5", 15x100mm axle, 100mm travel
HEADSET	ACROS AZF-604, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	BOOST 411K12C1800114, TA12x171.5, M12xP1.5x15.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO CUES RD-U8000, Shadow Plus Design
CRANKSET	ONE Sport, Alloy
CHAINRING	ONE Sport, 38T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	SHIMANO CN-LG500

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKES REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

### WHEELS

HUB FRONT	SHIMANO HB-MT410-B, 32H, CL, 15x110mm, THRU Type AXLE
RIMS FRONT	STARS J30D, Disc, 32H
TYRES FRONT	Schwalbe Hurricane Performance, 29x2.25, ADDIX
HUB REAR	SHIMANO FH-MT400-B, 32H, CL, 12x148mm, THRU Type AXLE
RIMS REAR	STARS J30D, Disc, 32H
TYRES REAR	Schwalbe Hurricane Performance, 29x2.25, ADDIX
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

### COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, Adjustable
HANDLEBAR	ONE Alloy, 25mm rise, 660mm, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

### PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEAT POST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	Marwi SP-610

## GEOMETRY

FRAME SIZE	S	M
WHEEL SIZE ToUpper()	29	29
SEAT TUBE LENGTH (mm) ToUpper()	381	457
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	570	590
STACK HEIGHT (mm) ToUpper()	643	652
REACH (mm) ToUpper()	382	399
SEAT TUBE ANGLE ToUpper()	73,7°	73,7°
HEAD TUBE ANGLE ToUpper()	67°	67°
REAR CENTER (mm) ToUpper()		
HEAD TUBE LENGTH (mm) ToUpper()	130	140
WHEELBASE (mm) ToUpper()	1176	1197

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# eBLOX 6.5

Gloss Petrol / Black

eTOUR / eBLOX



## SPECIFICATIONS

### BASE INFO

ESYSTEM	BOSCH CX Performance, Battery PowerTube 750Wh
DISTANCE	200km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### E- BIKE PARTS

MOTOR	BOSCH Performance Line CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 750Wh
DISPLAY	BOSCH Kiox 300

### FRAMESET

FRAME	Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RockShox Judy Silver TK, Tapered, SoloAir, 15x110mm axle, 100mm travel
HEADSET	ACROS AZF-604, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	BOOST 411K12C1800114, TA12x171.5, M12xP1.5x15.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 180mm
BRAKES REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 180mm

### WHEELS

HUB FRONT	SHIMANO HB-MT410-B, 32H, CL, 15x110mm, THRU Type AXLE
RIMS FRONT	STARS J30D, Disc, 32H
TYRES FRONT	Schwalbe G-One Allround Performance, 29x2.25
HUB REAR	SHIMANO FH-MT410-B, 32H, CL, 12x148mm, THRU Type AXLE
RIMS REAR	STARS J30D, Disc, 32H
TYRES REAR	Schwalbe G-One Allround Performance, 29x2.25
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

### COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, Adjustable
HANDLEBAR	ONE Alloy, 20mm rise, 680mm, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

### PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEAT POST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

### CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

## GEOMETRY

FRAME SIZE	S	M	L	XI
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	592	612	632	642
STACK HEIGHT (mm) ToUpper()	638	638	638	656
REACH (mm) ToUpper()	460	459	479	500
SEAT TUBE ANGLE ToUpper()	78°	77°	77°	78°
HEAD TUBE ANGLE ToUpper()	66°	66°	66°	66°
REAR CENTER (mm) ToUpper()				
HEAD TUBE LENGTH (mm) ToUpper()	120	120	120	140
WHEELBASE (mm) ToUpper()	1215	1215	1235	1264

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# eBLOX 6.5

Gloss White / Copper

eTOUR / eBLOX



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

ESYSTEM	BOSCH CX Performance, Battery PowerTube 750Wh
DISTANCE	200km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### E- BIKE PARTS

MOTOR	BOSCH Performance Line CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 750Wh
DISPLAY	BOSCH Kiox 300

### FRAMESET

FRAME	Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RockShox Judy Silver TK, Tapered, SoloAir, 15x110mm axle, 100mm travel
HEADSET	ACROS AZF-604, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	BOOST 411K12C1800114, TA12x171.5, M12xP1.5x15.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKES REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

### WHEELS

HUB FRONT	SHIMANO HB-MT410-B, 32H, CL, 15x110mm, THRU Type AXLE
RIMS FRONT	STARS J30D, Disc, 32H
TYRES FRONT	Schwalbe G-One Allround Performance, 29x2.25
HUB REAR	SHIMANO FH-MT410-B, 32H, CL, 12x148mm, THRU Type AXLE
RIMS REAR	STARS J30D, Disc, 32H
TYRES REAR	Schwalbe G-One Allround Performance, 29x2.25
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

### COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, Adjustable
HANDLEBAR	ONE Alloy, 20mm rise, 660mm, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

### PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEAT POST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

### CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

## GEOMETRY

FRAME SIZE	S	M
WHEEL SIZE ToUpper()	29	29
SEAT TUBE LENGTH (mm) ToUpper()	393	431
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	590	610
STACK HEIGHT (mm) ToUpper()	635	653
REACH (mm) ToUpper()	465	465
SEAT TUBE ANGLE ToUpper()	78,9°	77,5°
HEAD TUBE ANGLE ToUpper()	66°	66°
REAR CENTER (mm) ToUpper()		
HEAD TUBE LENGTH (mm) ToUpper()	120	140
WHEELBASE (mm) ToUpper()	1205	1213

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# eBLOX 6.3

Matte Black / Chrome

eTOUR / eBLOX



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

ESYSTEM	BOSCH Performance, Battery PowerTube 625Wh
DISTANCE	150km
MAX. TORQUE	75Nm / 300%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### E- BIKE PARTS

MOTOR	BOSCH Performance Line, 65Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 625Wh
DISPLAY	BOSCH Intuvia 100

### FRAMESET

FRAME	Alu 6061 T6, Comfort Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RST Volant, Tapered, 15x100mm axle, 80mm travel
HEADSET	ACROS AZF-604, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	BOOST 411K12C1800114, TA12x171.5, M12xP1.5x15.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO CUES RD-U8020, Shadow Plus Design
CRANKSET	ONE Sport, Alloy
CHAINRING	ONE Sport, 38T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-45T
CHAIN	SHIMANO CN-LG500

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKES REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

### WHEELS

HUB FRONT	SHIMANO HB-MT410, 32H, CL, 15x100mm, THRU Type AXLE
RIMS FRONT	STARS J30D, Disc, 32H
TYRES FRONT	Schwalbe G-One Allround Performance, 29x2.25
HUB REAR	SHIMANO FH-MT400-B, 32H, CL, 12x148mm, THRU Type AXLE
RIMS REAR	STARS J30D, Disc, 32H
TYRES REAR	Schwalbe G-One Allround Performance, 29x2.25
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

### COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, Adjustable
HANDLEBAR	ONE Alloy, 20mm rise, 680mm, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

### PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Alloy, 20mm rise, 680mm, 31.8mm
SEAT POST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

### CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

## GEOMETRY

FRAME SIZE	S	M	L	XI
WHEEL SIZE ToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm) ToUpper()	406	457	510	559
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	570	590	610	630
STACK HEIGHT (mm) ToUpper()	616	625	634	643
REACH (mm) ToUpper()	392	399	420	440
SEAT TUBE ANGLE ToUpper()	73,9°	73°	73,3°	73,5°
HEAD TUBE ANGLE ToUpper()	67°	67°	67°	67°
REAR CENTER (mm) ToUpper()				
HEAD TUBE LENGTH (mm) ToUpper()	130	140	150	160
WHEELBASE (mm) ToUpper()	1160	1185	1212	1233

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



# eBLOX 6.3

Matte Dark Berry

eTOUR / eBLOX



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

ESYSTEM	BOSCH Performance, Battery PowerTube 625Wh
DISTANCE	150km
MAX. TORQUE	75Nm / 300%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### E- BIKE PARTS

MOTOR	BOSCH Performance Line, 65Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 625Wh
DISPLAY	BOSCH Intuvia 100

### FRAMESET

FRAME	Alu 6061 T6, Comfort Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RST Volant, Tapered, 15x100mm axle, 80mm travel
HEADSET	ACROS AZF-604, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	BOOST 411K12C1800114, TA12x171.5, M12xP1.5x15.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO CUES RD-U8020, Shadow Plus Design
CRANKSET	ONE Sport, Alloy
CHAINRING	ONE Sport, 38T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-45T
CHAIN	SHIMANO CN-LG500

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKES REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

### WHEELS

HUB FRONT	SHIMANO HB-MT410, 32H, CL, 15x100mm, THRU Type AXLE
RIMS FRONT	STARS J30D, Disc, 32H
TYRES FRONT	Schwalbe G-One Allround Performance, 29x2.25
HUB REAR	SHIMANO FH-MT400-B, 32H, CL, 12x148mm, THRU Type AXLE
RIMS REAR	STARS J30D, Disc, 32H
TYRES REAR	Schwalbe G-One Allround Performance, 29x2.25
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

### COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, Adjustable
HANDLEBAR	ONE Alloy, 20mm rise, 660mm, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

### PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEAT POST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

### CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

## GEOMETRY

FRAME SIZE	S	M
WHEEL SIZE ToUpper()	29	29
SEAT TUBE LENGTH (mm) ToUpper()	406	457
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	570	590
STACK HEIGHT (mm) ToUpper()	606	625
REACH (mm) ToUpper()	390	410
SEAT TUBE ANGLE ToUpper()	73,5°	73,9°
HEAD TUBE ANGLE ToUpper()	67°	67°
REAR CENTER (mm) ToUpper()		
HEAD TUBE LENGTH (mm) ToUpper()	120	140
WHEELBASE (mm) ToUpper()	1169	1196

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# eBLOX 6.1

Matte Olive

eTOUR / eBLOX



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

ESYSTEM	BOSCH ACTIVE PLUS; Battery PowerTube 500Wh
DISTANCE	140km
MAX. TORQUE	50Nm / 270%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### E- BIKE PARTS

MOTOR	BOSCH Active Line Plus, 50Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 500Wh
DISPLAY	BOSCH Purion 200

### FRAMESET

FRAME	Alu 6061 T6, Comfort Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RST Volant, Tapered, 15x100mm axle, 80mm travel
HEADSET	ACROS AZF-604, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	BOOST 411K12C1800114, TA12x171.5, M12xP1.5x15.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4000-9R, RAPIDFIRE Plus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4000, Shadow Design
CRANKSET	ONE Sport, Alloy
CHAINRING	ONE Sport, 38T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-41T
CHAIN	SHIMANO CN-LG500

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKES REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

### WHEELS

HUB FRONT	SHIMANO HB-MT410, 32H, CL, 15x100mm, THRU Type AXLE
RIMS FRONT	STARS J30D, Disc, 32H
TYRES FRONT	Schwalbe G-One Bite, RaceGuard, 50-622, Reflective Tape
HUB REAR	SHIMANO FH-MT400-B, 32H, CL, 12x148mm, THRU Type AXLE
RIMS REAR	STARS J30D, Disc, 32H
TYRES REAR	Schwalbe G-One Bite, RaceGuard, 50-622, Reflective Tape
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

### COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, Adjustable
HANDLEBAR	ONE Alloy, 20mm rise, 680mm, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

### PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEAT POST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

### CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

## GEOMETRY

FRAME SIZE	S	M	L	XI
WHEEL SIZEToUpper()	29	29	29	29
SEAT TUBE LENGTH (mm)ToUpper()	406	457	510	559
EFFECTIVE TOP TUBE LENGTH (mm)ToUpper()	570	590	610	630
STACK HEIGHT (mm)ToUpper()	616	625	634	643
REACH (mm)ToUpper()	392	399	420	440
SEAT TUBE ANGLEToUpper()	73,9°	73°	73,3°	73,5°
HEAD TUBE ANGLEToUpper()	67°	67°	67°	67°
REAR CENTER (mm)ToUpper()				
HEAD TUBE LENGTH (mm)ToUpper()	130	140	150	160
WHEELBASE (mm)ToUpper()	1160	1185	1212	1233

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# eBLOX 6.1

Matte Almond

eTOUR / eBLOX



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

E-SYSTEM	BOSCH ACTIVE PLUS; Battery PowerTube 500Wh
DISTANCE	140km
MAX. TORQUE	50Nm / 270%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### E- BIKE PARTS

MOTOR	BOSCH Active Line Plus, 50Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 500Wh
DISPLAY	BOSCH Purion 200

### FRAMESET

FRAME	Alu 6061 T6, Comfort Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RST Volant, Tapered, 15x100mm axle, 80mm travel
HEADSET	ACROS AZF-604, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	BOOST 411K12C1800114, TA12x171.5, M12xP1.5x15.5L, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4000-9R, RAPIDFIRE Plus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4000, Shadow Design
CRANKSET	ONE Sport, Alloy
CHAINRING	ONE Sport, 38T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-41T
CHAIN	SHIMANO CN-LG500

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKES REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

### WHEELS

HUB FRONT	SHIMANO HB-MT410, 32H, CL, 15x100mm, THRU Type AXLE
RIMS FRONT	STARS J30D, Disc, 32H
TYRES FRONT	Schwalbe G-One Bite, RaceGuard, 50-622, Reflective Tape
HUB REAR	SHIMANO FH-MT400-B, 32H, CL, 12x148mm, THRU Type AXLE
RIMS REAR	STARS J30D, Disc, 32H
TYRES REAR	Schwalbe G-One Bite, RaceGuard, 50-622, Reflective Tape
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

### COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, Adjustable
HANDLEBAR	ONE Alloy, 20mm rise, 660mm, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

### PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEAT POST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

### CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

## GEOMETRY

FRAME SIZE	S	M
WHEEL SIZE ToUpper()	29	29
SEAT TUBE LENGTH (mm) ToUpper()	406	457
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	570	590
STACK HEIGHT (mm) ToUpper()	606	625
REACH (mm) ToUpper()	390	410
SEAT TUBE ANGLE ToUpper()	73,5°	73,9°
HEAD TUBE ANGLE ToUpper()	67°	67°
REAR CENTER (mm) ToUpper()		
HEAD TUBE LENGTH (mm) ToUpper()	120	140
WHEELBASE (mm) ToUpper()	1169	1196

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

## SPECIFICATIONS

## BASE INFO

ESYSTEM	SHIMANO STEPS E6100, Battery DARFON 504Wh
DISTANCE	185km
MAX. TORQUE	60Nm / 200%
SUPPORT UP TO SPEED	25km/h

## ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

## E- BIKE PARTS

MOTOR	SHIMANO STEPS E6100, 60Nm
CHARGER	DARFON 2A
BATTERY	DARFON, 504Wh
DISPLAY	SHIMANO SC-E5000

## FRAMESET

FRAME	Alu X6 Ultralite, Advanced eMTB Geometry, SHIMANO STEPS ready, Integrated battery, SR dropout, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	SR Suntour NEX E-25, Tapered, Coil, QR Type, 63mm travel
HEADSET	ACROS AZF-604, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	BOOST 411K12C1800114, TA12x171.5, M12xP1.5x15.5L, Black

## DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4000-9R, RAPIDFIRE Plus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4000, Shadow Design
CRANKSET	SHIMANO FC-E6100, Black
CHAINRING	ONE Sport, 38T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-41T
CHAIN	SHIMANO CN-LG500

## BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKES REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

## WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QR Type
RIMS FRONT	STARS J30D, Disc, 32H
TYRES FRONT	Schwalbe G-One Bite, RaceGuard, 50-622, Reflective Tape
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIMS REAR	STARS J30D, Disc, 32H
TYRES REAR	Schwalbe G-One Bite, RaceGuard, 50-622, Reflective Tape
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

## COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, Adjustable
HANDLEBAR	ONE Alloy, 20mm rise, 680mm, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

## PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEAT POST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

## CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

## GEOMETRY

FRAME SIZE	M	L
WHEEL SIZE ToUpper()	28	28
SEAT TUBE LENGTH (mm) ToUpper()	431	482
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	590	610
STACK HEIGHT (mm) ToUpper()	604	604
REACH (mm) ToUpper()	411	431
SEAT TUBE ANGLE ToUpper()	73,5	73,5
HEAD TUBE ANGLE ToUpper()	68	68
REAR CENTER (mm) ToUpper()		
HEAD TUBE LENGTH (mm) ToUpper()	120	120
WHEELBASE (mm) ToUpper()	1126	1146



# eWAY 6.6

Matte Black

eTOUR / eWAY



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

ESYSTEM	BOSCH Performance, Battery PowerTube 625Wh
DISTANCE	150km
MAX. TORQUE	75Nm / 300%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 1 Suitable Road Riding

### E- BIKE PARTS

MOTOR	BOSCH Performance Line, 65Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 625Wh
DISPLAY	BOSCH Intuiva 100

### FRAMESET

FRAME	Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	SR Suntour NEX-DS, 1-1/8", Coil, QR Type, 50mm travel

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-10R, RAPIDFIRE Plus, 10-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6020, Shadow Design
CRANKSET	ONE, Alloy
CHAINRING	ONE, 44T
CASSETTE	SHIMANO CUES CS-LG400, 10-speed, 11-39T
CHAIN	SHIMANO CN-LG500

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKES REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

### WHEELS

HUB FRONT	SHIMANO HB-QC300, 36H, CL, M9X100mm, QR Type
RIMS FRONT	STARS J30D, Disc, 36H
TYRES FRONT	SCALATO DIVERSO, 50-622, Reflective Tape
HUB REAR	SHIMANO FH-QC300-HM, 36H, CL, M10X135mm, QR Type
RIMS REAR	STARS J30D, Disc, 36H
TYRES REAR	SCALATO DIVERSO, 50-622, Reflective Tape
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

### COCKPIT

STEM	ONE, Alloy, 31.8mm, Adjustable
HANDLEBAR	ONE Alloy, 25mm rise, 620mm, 31.8mm
GRIPS LEFT	ONE Race Ergo, Lock-On
GRIPS RIGHT	ONE Race Ergo, Lock-On

### PARTS

SADDLE	Selle Royal Hertz
SEAT POST	ONE, Alloy, Suspension, 30,9mm
SEAT POST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	Marwi SP-890

### CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR4 E, 120lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

## GEOMETRY

FRAME SIZE	S	M	L
WHEEL SIZE ToUpper()	700c	700c	700c
SEAT TUBE LENGTH (mm) ToUpper()	460	500	540
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	580	600	620
STACK HEIGHT (mm) ToUpper()	604	626	648
REACH (mm) ToUpper()	390	397	403
SEAT TUBE ANGLE ToUpper()	72,5°	72°	71,5°
HEAD TUBE ANGLE ToUpper()	69°	69,8°	70,5°
REAR CENTER (mm) ToUpper()	485	485	485
HEAD TUBE LENGTH (mm) ToUpper()	170	180	190
WHEELBASE (mm) ToUpper()	1127	1133	1139

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# eWAY 6.5

Gloss Grey

eTOUR / eWAY



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

ESYSTEM	BOSCH Performance, Battery PowerTube 625Wh
DISTANCE	150km
MAX. TORQUE	75Nm / 300%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 1 Suitable Road Riding

### E- BIKE PARTS

MOTOR	BOSCH Performance Line, 65Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 625Wh
DISPLAY	BOSCH Intuiva 100

### FRAMESET

FRAME	Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	SR Suntour NEX-DS, 1-1/8", Coil, QR Type, 50mm travel

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO NEXUS SL-C6000-8, REVOSHIFT, 8-speed
CRANKSET	ONE Sport, Alloy
CHAINRING	Gates CARBON DRIVE CDX, 50T
CASSETTE	Gates CARBON DRIVE CDX, 24T
CHAIN	Gates CARBON DRIVE CDX

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKES REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

### WHEELS

HUB FRONT	ONE, 36H, CL, M9X100mm, QR Type
RIMS FRONT	STARS J30D, Disc, 36H
TYRES FRONT	SCALATO DIVERSO, 50-622, Reflective Tape
HUB REAR	SHIMANO NEXUS SG-C6001-8D, 36H, CL, 135x187mm
RIMS REAR	STARS J30D, Disc, 36H
TYRES REAR	SCALATO DIVERSO, 50-622, Reflective Tape
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

### COCKPIT

STEM	ONE, Alloy, 31.8mm, Adjustable
HANDLEBAR	ONE Alloy, 25mm rise, 620mm, 31.8mm
GRIPS LEFT	ONE Race Ergo, Lock-On
GRIPS RIGHT	ONE Race Ergo, Lock-On

### PARTS

SADDLE	Selle Royal Hertz
SEATPOST	ONE, Alloy, Suspension, 30,9mm
SEAT POST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	Marwi SP-823

### CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

## GEOMETRY

FRAME SIZE	S	M	L
WHEEL SIZE ToUpper()	700c	700c	700c
SEAT TUBE LENGTH (mm) ToUpper()	460	500	540
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	580	600	620
STACK HEIGHT (mm) ToUpper()	604	626	648
REACH (mm) ToUpper()	390	397	403
SEAT TUBE ANGLE ToUpper()	72,5°	72°	71,5°
HEAD TUBE ANGLE ToUpper()	69°	69,8°	70,5°
REAR CENTER (mm) ToUpper()	485	485	485
HEAD TUBE LENGTH (mm) ToUpper()	170	180	190
WHEELBASE (mm) ToUpper()	1127	1133	1139

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

E-SYSTEM	BOSCH ACTIVE PLUS; Battery PowerTube 500Wh
DISTANCE	140km
MAX. TORQUE	50Nm / 270%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 1 Suitable Road Riding

### E- BIKE PARTS

MOTOR	BOSCH Active Line Plus, 50Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 500Wh
DISPLAY	BOSCH Purion 200

### FRAMESET

FRAME	Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	SR Suntour NEX-DS, 1-1/8", Coil, QR Type, 50mm travel

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO NEXUS SL-C3000-7 Revoshift, 7-speed
CRANKSET	ONE, Alloy
CHAINRING	ONE, 38T
CASSETTE	KMC, Sprocket, 18T
CHAIN	KMC Z1eHX

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKES REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

### WHEELS

HUB FRONT	ONE, 36H, CL, M9X100mm, QR Type
RIMS FRONT	STARS J30D, Disc, 36H
TYRES FRONT	SCALATO DIVERSO, 50-622, Reflective Tape
HUB REAR	SHIMANO NEXUS SG-C3001-7D, 36H, CL, 135x187mm
RIMS REAR	STARS J30D, Disc, 36H
TYRES REAR	SCALATO DIVERSO, 50-622, Reflective Tape
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

### COCKPIT

STEM	ONE, Alloy, 31.8mm, Adjustable
HANDLEBAR	ONE Alloy, 25mm rise, 620mm, 31.8mm
GRIPS LEFT	ONE Race Ergo, Lock-On
GRIPS RIGHT	ONE Race Ergo, Lock-On

### PARTS

SADDLE	Selle Royal Hertz
SEATPOST	ONE, Alloy, 30,9mm
SEAT POST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	Marwi SP-823

### CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR4 E, 120lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

## GEOMETRY

FRAME SIZE	S	M	L
WHEEL SIZE ToUpper()	700c	700c	700c
SEAT TUBE LENGTH (mm) ToUpper()	460	500	540
EFFECTIVE TOP TUBE LENGTH (mm) ToUpper()	580	600	620
STACK HEIGHT (mm) ToUpper()	604	626	648
REACH (mm) ToUpper()	390	397	403
SEAT TUBE ANGLE ToUpper()	72,5°	72°	71,5°
HEAD TUBE ANGLE ToUpper()	69°	69,8°	70,5°
REAR CENTER (mm) ToUpper()	485	485	485
HEAD TUBE LENGTH (mm) ToUpper()	170	180	190
WHEELBASE (mm) ToUpper()	1127	1133	1139

# iXF 9.8

Matte Berry Carbon

iMTB FULL SUSPENSION | Light / iXF



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

ESYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh
MAX. TORQUE	55Nm / 300%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Mini Remote

### FRAMESET

FRAME	Carbon MTB DC SU-E10-01; Advanced Down Country Geometry, Travel 140 mm, Integrated Cable routing, BB92, 3D one piece link, Carbon swingarm, UDH dropout, Boost Thru Axle 148x12 mm, Dropped seat post ready
SUSPENSION FORK	DT Swiss F535 ONE, Tapered, 15x110mm axle, 150mm travel
REAR SHOCK	DT Swiss R535 ONE, size 210x55mm
HEADSET	ACROS AZX-1051S, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°, Stainless Bearings
REAR AXLE	SB01, TA12x175.5, M12xP1.0x14.5mm, Black

### DRIVETRAIN

SHIFTERS RIGHT	SRAM AXS ROCKER, 12-speed
REAR DERAILLEUR	SRAM X0 EAGLE AXS T-Type
CRANKSET	ONE Race, Alloy
CHAINRING	SRAM T-TYPE, 36T
CASSETTE	SRAM X0 XS-1295, 12-speed, T-Type, 10-52T
CHAIN	SRAM X0, T-Type

### BRAKING SYSTEM

BRAKES FRONT	SRAM LEVEL SILVER STEALTH, 4 piston, hydraulic disc brake
ROTOR FRONT	SRAM HS2, 180mm
BRAKES REAR	SRAM LEVEL SILVER STEALTH, 4 piston, hydraulic disc brake
ROTOR REAR	SRAM HS2, 180mm

### WHEELS

WHEELSET FRONT	DT Swiss Hybrid MTB HXC 1501 SPLINE®, Carbon, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss Hybrid MTB HXC 1501 SPLINE®, Carbon, CL, 12x148mm, SRAM XD, Tubeless Ready
TYRES FRONT	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip
TYRES REAR	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip

### COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

### PARTS

SADDLE	Fizik Aidon X5, Alloy
SEAT POST LEVER	SRAM AXS ROCKER, Dropper Post Lever
SEATPOST	SRAM Reverb AXS dropper post, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

## GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	420	440	460
EFFECTIVE TOP TUBE LENGTH (MM)	574	590	625	652
STACK HEIGHT (MM)	606	605	636	645
REACH (MM)	450	465	490	515
SEAT TUBE ANGLE	78°	78°	78°	78°
HEAD TUBE ANGLE	64,5°	64,5°	64,5°	64,5°
REAR CENTER (MM)	450	450	450	450
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1223	1239	1274	1301

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



# iXF 9.7

Matte Carbon

iMTB FULL SUSPENSION | Light / iXF



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

ESYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh
MAX. TORQUE	55Nm / 300%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Mini Remote

### FRAMESET

FRAME	Carbon MTB DC SU-E10-01; Advanced Down Country Geometry, Travel 140 mm, Integrated Cable routing, BB92, 3D one piece link, Carbon swingarm, UDH dropout, Boost Thru Axle 148x12 mm, Dropped seat post ready
SUSPENSION FORK	DT Swiss F535 ONE, Tapered, 15x110mm axle, 150mm travel
REAR SHOCK	DT Swiss R535 ONE, size 210x55mm
HEADSET	ACROS AZX-1051S, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°, Stainless Bearings
REAR AXLE	SB01, TA12x175.5, M12xP1.0x14.5mm, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SLX SL-M7100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO XT M8220, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 180mm
BRAKES REAR	SHIMANO XT M8220, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

### WHEELS

WHEELSET FRONT	DT Swiss Hybrid MTB H 1900 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss Hybrid MTB H 1900 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TYRES FRONT	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip
TYRES REAR	Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip

### COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 760mm, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

### PARTS

SADDLE	Fizi:k Aidon X5, Alloy
SEAT POST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

## GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	420	440	460
EFFECTIVE TOP TUBE LENGTH (MM)	574	590	625	652
STACK HEIGHT (MM)	606	605	636	645
REACH (MM)	450	465	490	515
SEAT TUBE ANGLE	78°	78°	78°	78°
HEAD TUBE ANGLE	64,5°	64,5°	64,5°	64,5°
REAR CENTER (MM)	450	450	450	450
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1223	1239	1274	1301

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# iXF 9.2

Matte Green Grey

iMTB FULL SUSPENSION | Light / iXF



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

ESYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh
MAX. TORQUE	55Nm / 300%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 3 For rough Off-Road riding and jumps less than 61cm (24")

### E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Mini Remote

### FRAMESET

FRAME	Carbon MTB DC SU-E10-01; Advanced Down Country Geometry, Travel 140 mm, Integrated Cable routing, BB92, 3D one piece link, Carbon swingarm, UDH dropout, Boost Thru Axle 148x12 mm, Dropped seat post ready
SUSPENSION FORK	RockShox 35 Silver TK, Tapered, SoloAir, 15x110mm axle, 140mm travel
REAR SHOCK	RockShox Deluxe Select+ RT, size 210x55mm
HEADSET	ACROS AZX-1051S, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°, Stainless Bearings
REAR AXLE	SB01, TA12x175.5, M12xP1.0x14.5mm, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKES REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 180mm

### WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIMS FRONT	BLACK JACK Ready 30, Disc, 32H, Tubeless Ready
TYRES FRONT	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIMS REAR	BLACK JACK Ready 30, Disc, 32H, Tubeless Ready
TYRES REAR	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

### COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 760mm, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

### PARTS

SADDLE	Fizi:k Aidon X5, Alloy
SEAT POST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEAT POST CLAMP	ONE CC-080A, 34.9mm, Black

## GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	420	440	460
EFFECTIVE TOP TUBE LENGTH (MM)	574	590	625	652
STACK HEIGHT (MM)	606	605	636	645
REACH (MM)	450	465	490	515
SEAT TUBE ANGLE	78°	78°	78°	78°
HEAD TUBE ANGLE	64,5°	64,5°	64,5°	64,5°
REAR CENTER (MM)	450	450	450	450
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1223	1239	1274	1301

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# iBLOX 6.5

Gloss Grey

iTOUR | Light / iXR



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

ESYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh
MAX. TORQUE	55Nm / 300%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Kiox 300

### FRAMESET

FRAME	Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RockShox Judy Silver TK, Tapered, SoloAir, 15x110mm axle, 100mm travel
HEADSET	ACROS AZX-1051, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 180mm
BRAKES REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 180mm

### WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIMS FRONT	STARS J30D, Disc, 32H
TYRES FRONT	Schwalbe G-One Allround Performance, 29x2.25
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIMS REAR	STARS J30D, Disc, 32H
TYRES REAR	Schwalbe G-One Allround Performance, 29x2.25
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

### COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, 0°
HANDLEBAR	ONE Alloy, 20mm rise, 680mm, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

### PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEAT POST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

### CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR4 E, 120lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

## GEOMETRY

FRAME SIZE	14" (XS)	16" (S)	18" (M)	20" (L)	22" (XL)
WHEEL SIZE	29	29	29	29	29
SEAT TUBE LENGTH (MM)	365	406	457	508	559
EFFECTIVE TOP TUBE LENGTH (MM)	550	570	590	610	630
STACK HEIGHT (MM)	632	642	651	660	670
REACH (MM)	369	386	403	421	438
SEAT TUBE ANGLE	74°	74°	74°	74°	74°
HEAD TUBE ANGLE	69°	69°	69°	69°	69°
REAR CENTER (MM)	450	450	450	450	450
HEAD TUBE LENGTH (MM)	110	120	130	140	150
WHEELBASE (MM)	1081	1102	1123	1144	1165

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# iBLOX 6.5

Gloss Grey

iTOUR | Light / iXR



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

ESYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh
MAX. TORQUE	55Nm / 300%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Kiox 300

### FRAMESET

FRAME	Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RockShox Judy Silver TK, Tapered, SoloAir, 15x110mm axle, 100mm travel
HEADSET	ACROS AZX-1051, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 180mm
BRAKES REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 180mm

### WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIMS FRONT	STARS J30D, Disc, 32H
TYRES FRONT	Schwalbe G-One Allround Performance, 29x2.25
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12x148mm, THRU Type AXLE
RIMS REAR	STARS J30D, Disc, 32H
TYRES REAR	Schwalbe G-One Allround Performance, 29x2.25
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

### COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, 0°
HANDLEBAR	ONE Alloy, 20mm rise, 660mm, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

### PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEAT POST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

### CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR4 E, 120lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

## GEOMETRY

FRAME SIZE	15" (S)	16" (M)	18" (L)
WHEEL SIZE	29	29	29
SEAT TUBE LENGTH (MM)	381	457	496
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610
STACK HEIGHT (MM)	642	651	660
REACH (MM)	386	403	421
SEAT TUBE ANGLE	74°	74°	74°
HEAD TUBE ANGLE	69°	69°	69°
REAR CENTER (MM)	450	450	450
HEAD TUBE LENGTH (MM)	120	130	140
WHEELBASE (MM)	1102	1123	1144

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.



# iBLOX 6.3

Matte Black

iTOUR | Light / iXR



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

ESYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh
MAX. TORQUE	55Nm / 300%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Purion 200

### FRAMESET

FRAME	Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RST Volant, Tapered, 15x100mm axle, 80mm travel
HEADSET	ACROS AZX-1051, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO CUES RD-U8000, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-45T
CHAIN	SHIMANO CN-LG500

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKES REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

### WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIMS FRONT	STARS J30D, Disc, 32H
TYRES FRONT	Schwalbe G-One Allround Performance, 29x2.25
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIMS REAR	STARS J30D, Disc, 32H
TYRES REAR	Schwalbe G-One Allround Performance, 29x2.25
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

### COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, 0°
HANDLEBAR	ONE Alloy, 20mm rise, 680mm, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

### PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 30,9mm
SEAT POST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

### CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR4 E, 120lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

## GEOMETRY

FRAME SIZE	14" (XS)	16" (S)	18" (M)	20" (L)	22" (XL)
WHEEL SIZE	29	29	29	29	29
SEAT TUBE LENGTH (MM)	365	406	457	508	559
EFFECTIVE TOP TUBE LENGTH (MM)	550	570	590	610	630
STACK HEIGHT (MM)	632	642	651	660	670
REACH (MM)	369	386	403	421	438
SEAT TUBE ANGLE	74°	74°	74°	74°	74°
HEAD TUBE ANGLE	69°	69°	69°	69°	69°
REAR CENTER (MM)	450	450	450	450	450
HEAD TUBE LENGTH (MM)	110	120	130	140	150
WHEELBASE (MM)	1081	1102	1123	1144	1165

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# iXR 6.7

Matte Trooper Green / Black

iGRAVEL | Light / iX-ROAD



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

ESYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh
MAX. TORQUE	55Nm / 300%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Mini Remote, Drop Bar

### FRAMESET

FRAME	Alloy double-butted, Gravel Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, SH dropout, Integrated Cable Routing, Bike packing and mudguards ready
FORK	Rigid X6 Alloy
HEADSET	ACROS AZX-1090S ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, STAINLESS BEARINGS, BLACK
FRONT AXLE	SB02, TA12x125, M12xP1.5x10L, Black
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO GRX RX825, Di2, 12-speed
REAR DERAILLEUR	SHIMANO GRX RD-RX827, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T
CASSETTE	SHIMANO XT CS-M8200, 12-speed, 9-45T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO GRX RX825, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-CL800, 160mm
BRAKES REAR	SHIMANO GRX RX825, hydraulic disc brake
ROTOR REAR	SHIMANO RT-CL800, 160mm

### WHEELS

WHEELSET FRONT	DT Swiss HG 1800 SPLINE®, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss HG 1800 SPLINE®, CL, 12x142mm, SH12, Tubeless Ready
TYRES FRONT	Schwalbe G-One Allround Performance, RaceGuard, TL-Easy, 45-622, ADDIX
TYRES REAR	Schwalbe G-One Allround Performance, RaceGuard, TL-Easy, 45-622, ADDIX

### COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm
GRIPS LEFT	ONE Handlebar Tape

### PARTS

SADDLE	Fizik Terra Argo X5, Alloy
SEATPOST	ONE Sport, Alloy, 30,9mm
SEAT POST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black

## GEOMETRY

FRAME SIZE	470mm (XS)	490" (S)	510" (M)	530mm (L)	550mm (XL)
WHEEL SIZE	700c	700c	700c	700c	700c
SEAT TUBE LENGTH (MM)	470	490	510	530	550
EFFECTIVE TOP TUBE LENGTH (MM)	530	540	550	570	590
STACK HEIGHT (MM)	553	564	574	595	616
REACH (MM)	377	378	380	394	402
SEAT TUBE ANGLE	74,5°	74°	73,5°	73,5°	73°
HEAD TUBE ANGLE	70°	70,5°	70,5°	71°	71,5°
REAR CENTER (MM)	445	445	445	445	445
HEAD TUBE LENGTH (MM)	110	120	130	150	170
WHEELBASE (MM)	1039	1040	1045	1045	1070

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.

# iXR 6.5

Matte Green Grey

iGRAVEL | Light / iX-ROAD



COMPUTER VISUALIZATION

## SPECIFICATIONS

### BASE INFO

ESYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh
MAX. TORQUE	55Nm / 300%
SUPPORT UP TO SPEED	25km/h

### ISO AND ASTM NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
ASTM norm	ASTM 2 For on and Off-Road riding and drops less than 15cm (6")

### E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Mini Remote, Drop Bar

### FRAMESET

FRAME	Alloy double-butted, Gravel Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, SH dropout, Integrated Cable Routing, Bike packing and mudguards ready
SUSPENSION FORK	RockShox RUDY Base, Tapered, SoloAir, 12x100mm axle, 40mm travel
HEADSET	ACROS AZX-1090S ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, STAINLESS BEARINGS, BLACK
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

### DRIVETRAIN

SHIFTERS RIGHT	SHIMANO GRX RX610, 12-speed
REAR DERAILLEUR	SHIMANO GRX RD-RX822, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T
CASSETTE	SHIMANO SLX CS-M7101, 12-speed, 10-42T
CHAIN	SHIMANO DEORE CN-M6100

### BRAKING SYSTEM

BRAKES FRONT	SHIMANO GRX RX610, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 160mm
BRAKES REAR	SHIMANO GRX RX610, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 160mm

### WHEELS

WHEELSET FRONT	DT Swiss HG 1800 SPLINE®, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss HG 1800 SPLINE®, CL, 12x142mm, SH12, Tubeless Ready
TYRES FRONT	Schwalbe G-One Allround Performance, RaceGuard, TL-Easy, 45-622, ADDIX
TYRES REAR	Schwalbe G-One Allround Performance, RaceGuard, TL-Easy, 45-622, ADDIX

### COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm
GRIPS LEFT	ONE Handlebar Tape

### PARTS

SADDLE	Selle Royal Gravel
SEATPOST	ONE Sport, Alloy, 30,9mm
SEAT POST CLAMP	ONE CC-617, 34,9mm, with Quick Release level, Black

## GEOMETRY

FRAME SIZE	470mm (XS)	490° (S)	510° (M)	530mm (L)	550mm (XL)
WHEEL SIZE	700c	700c	700c	700c	700c
SEAT TUBE LENGTH (MM)	470	490	510	530	550
EFFECTIVE TOP TUBE LENGTH (MM)	530	540	550	570	590
STACK HEIGHT (MM)	553	564	574	595	616
REACH (MM)	377	378	380	394	402
SEAT TUBE ANGLE	74,5°	74°	73,5°	73,5°	73°
HEAD TUBE ANGLE	70°	70,5°	70,5°	71°	71,5°
REAR CENTER (MM)	445	445	445	445	445
HEAD TUBE LENGTH (MM)	110	120	130	150	170
WHEELBASE (MM)	1039	1040	1045	1045	1070

\* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.





Každý z nás má různé potřeby a očekávání, ale sdílíme společný cíl: co nejvíce si užít den na kole. Proto jsou naše oblečení a helmy dokonale padnoucí, pohodlné a vysoce kvalitní. A dokonale ladí s koly Superior. Abychom pokryli všechny potřeby a situace, které se na kole mohou vyskytnout, vyvíjíme příslušenství ONE Bikeparts. Vyladíme každý detail tak, aby když budete potřebovat světlo, brašnu nebo nástroj, fungovalo tak, jak má, a překvapilo vás chytrými funkcemi.





\* Specifikace, barvy a dostupnost produktů se mohou změnit bez předchozího upozornění.  
Pro dostupnost a ceny kontaktujte prosím prodejce ve vašem městě / zemi.

Oficiální distributor: LEVELSPORTKONCEPT s.r.o.,  
K Bílému vrchu 2978/5, 193 00 Praha 9 - Horní Počernice,  
E: [info@levelsportkoncept.cz](mailto:info@levelsportkoncept.cz), T: +420 284 840 310,  
[www.levelsportkoncept.cz](http://www.levelsportkoncept.cz)

[www.superiorbikes.com](http://www.superiorbikes.com)